

# TLK 110

**A DEVICE DESIGNED FOR YOU AND BUILT TO LAST**



The TLK 110 combines the flexibility of push-to-talk communication via broadband with the reliability of a rugged, purpose-built radio. With its effortless device management capabilities, the TLK 110 can be optimized for seamless operations, leaving your business safer, smarter and better connected.

## KEY FEATURES



### COMMUNICATION WITHOUT LIMITS

- Nationwide push-to-talk via broadband
- 4G network speed
- Wi-Fi calling over 2.4 + 5 GHz networks
- Intelligent VOX PTT
- Ergonomically designed
- AI-based noise suppression
- Wideband Speaker



### DESIGNED FOR YOU, BUILT TO LAST

- Emergency calling
- Dedicated emergency button
- Man Down/Fall Alert
- Lone Worker
- 18-hour battery life
- Ergonomically designed
- 2-line monochrome display
- IP67 rating
- Antimicrobial housing



### DEVICES MANAGED WITH EASE

- Centralised device provisioning
- Remote software updates
- Remote talkgroup setup
- GPS/GNSS location tracking
- Location-based talkgroups
- Interoperable with smartphones/tablets via WAVE PTX™
- WAVE PTX dispatch compatible



GENERAL SPECIFICATIONS

Network	3G B1,B2,B4,B5,B8 4G FDD-B2,B4,B5,B7,B12,B13,B17,B25,B26,B66,TDD-B41
Channel Capacity	96 Channels
Contact List	1000 Contacts
Dimensions	Without Antenna: Height: 5.3" (134mm) Width: 2.3" (58mm) Depth: 1.0" (24mm)  With Antenna: Height: 6.7" (171mm) Width: 2.3" (58mm) Depth: 1.0" (24mm)
Weight with Battery	6.95 oz (197g)
Battery Capacity	3.7V (Nominal) 2500 mAh with PMNN4578
Battery (2500mAh Li-Ion Battery) Operating Hours 5:5:90 Duty Cycle <sup>1</sup>	18 hours
IP Rating	IP67
Ports	USB Type-C (use for charging) 2.5mm audio jack with mechanical lock (use for audio accessories)
Sensor	Accelerometer
SIM	1x 3FF-Micro SIM
Encryption	Powered by WAVE PTX
Apps	AES 256
Models Available	Pre-installed SIM included in WAVE PTX subscription <sup>2</sup>

AUDIO SPECIFICATIONS

Digital Vocoder Type	AMR-WB, OPUS
Audio Response (3GPP TS 26.131)	5.4.6
Audio Output Power (Rated/Max)	1W/2.5W
Audio Distortion at Rated Audio	<5%
Maximum Speech Loudness by Default (ISO532B)	96 phon

MILITARY STANDARD (MIL-STD 810)

	MIL-STD810C		MIL-STD810D		MIL-STD 810E		MIL-STD 810F		MIL-STD 810G		MIL-STD 810H	
	METHOD	PROCEDURE	METHOD	PROCEDURE	METHOD	PROCEDURE	METHOD	PROCEDURE	METHOD	PROCEDURE	METHOD	PROCEDURE
Low Pressure	500.1	I	500.2	II	500.3	II	500.4	II	500.6	II	500.6	II
High Temp	501.1	I, II	501.2	I/A1, II/A1	501.3	I/A1, II/A1	501.4	I/Hot, II/Hot	501.6	I/A1, II/A1	501.7	I/A1, II/A1
Low Temp	502.1	I	502.2	I, II	502.3	I, II	502.4	I, II	502.6	I, II	502.7	I, II
Temp Shock	503.1	I	503.2	A1/C3	503.3	A1/C3	503.4	I	503.6	I-C	503.7	I-C
Solar Radiation	505.1	II	505.2	I/A1	505.3	I/A1	505.4	I/A1	505.6	I/A1	505.7	I/A1
Rain	506.1	I, II	506.2	I, II	506.3	I, II	506.4	I, III	506.6	I, III	506.6	I, III
Humidity	507.1	II	507.2	II	507.3	II	507.4	-	507.6	II/Aggravated	507.6	II/Aggravated
Salt Fog	509.1	I	509.2	I	509.3	I	509.4	-	509.6	-	509.7	-
Blowing Dust & Sand	510.1	I/-	510.2	I, II	510.3	I, II	510.4	I, II	510.6	I, II	510.7	I, II
Vibration	514.2	VIII/CatF, XI	514.3	I/Cat10, II/Cat3	514.4	I/Cat10, III/Cat3	514.5	I/Cat24, II/Cat5	514.7	I/Cat24, II/Cat5	514.8	I/Cat24, II/Cat5
Shock	516.2	I, II	516.3	I, IV	516.4	I, IV	516.5	I, IV	516.7	I, IV	516.8	I, IV
Contamination by Fluids	-	-	-	-	-	-	-	-	504.2	II	504.3	2.2.6 b

WI-FI SPECIFICATIONS

Frequency Range	2.4 GHz, 5GHz
Standards Supported	802.11 a, b, g, n, ac
Security Protocol Supported	WPA2 (personal and enterprise), WPA3 (personal)
Maximum Number of SSIDs	5

BLUETOOTH + GNSS SPECIFICATIONS

Version	v4.2 (BR/EDR+BLE)
Range	10m
Supported Profiles	BLE, SPP, HSP
Simultaneous Connections	1 per profile
Constellation Support	GPS, GLONASS, Galileo, Beidou, A-GNSS
Time to First Fix, Cold Start	60s
Time to First Fix, Hot Start	10s
Horizontal Accuracy	5m

ENVIRONMENTAL SPECIFICATIONS

Operating Temperature	-20°C to 60°C (radio) / -10°C to 60°C (with battery)
Storage Temperature	-40°C to 85°C
Thermal Shock	Per MIL-STD 810
Humidity	Per MIL-STD 810
Electrostatic Discharge	Per MIL-STD 810
Dust and Water Intrusion	IP67
Packaging Test	Per MIL-STD 810

1 Battery life may vary depending on use and conditions  
2 Coverage limited to NA and CA separately, will vary depending on conditions





## TLK 110 ACCESSORIES

Further improve your organisation's flexibility with the TLK 110's accessory offerings. The TLK 110 is compatible with a variety of accessories from earpieces and headphones to batteries, power supplies and antennas, so you can find the product that works best for you and your workforce.

### AUDIO

#### PMLN7159

Adjustable D-style Earpiece with In-Line Microphone and Push-to-Talk




#### PMLN8298

WP300 Wireless Bluetooth Control Pod with PTT Button<sup>3</sup>



### ANTENNA



32012144001	Grey Antenna ID, Pack of 10 units
32012144002	Yellow Antenna ID, Pack of 10 units
32012144003	Green Antenna ID, Pack of 10 units
32012144004	Blue Antenna ID, Pack of 10 units
32012144005	Purple Antenna ID, Pack of 10 units

### ENERGY

#### PMLN8569

TLK 110 6-Pocket Multi-Unit Charger



#### PMNN4578

Lithium Ion 2500 mAh Battery



### CARRY

#### PMLN7128

Heavy Duty Swivel Belt Clip



<sup>3</sup> WP300 requires compatible earpiece: PMLN8190, PMLN8077 or PMLN8125

# ADDITIONAL COMPATIBLE ACCESSORIES FOR TLK 110

## WIRED AUDIO ACCESSORIES

<b>PMLN7156</b>	Mag One Earbud with In-Line Microphone and Push-To-Talk, Black
<b>PMLN7189</b>	Swivel Earpiece with In-Line Microphone and Push-To-Talk
<b>PMLN7157</b>	2-Wire Surveillance Kit, Black
<b>PMLN7158</b>	1-Wire Surveillance Kit, Black
<b>PMLN8191</b>	1-Wire Clear Tube Earpiece, 2.5mm Angled Single Pin
<b>PMMN4125</b>	RM250 Wired Remote Speaker Microphone, Large (IP67)

## WIRELESS AND SECONDARY AUDIO ACCESSORIES

<b>PMMN4127</b>	WM500 Wireless Remote Speaker Microphone
<b>PMLN8123</b>	EP910W Wireless Earpiece PTT
<b>PMLN7560</b>	Receive-Only Earpiece with Translucent Tube and Rubber Eartip for RM250 and WM500 RSMs
<b>PMLN8077</b>	Single Pin Over-the-Ear Earpiece for WP300 Bluetooth Control Pod
<b>PMLN8125</b>	Single Pin Short Cord Earpiece for WP300 Bluetooth Control Pod
<b>PMLN8190</b>	1-Wire Clear Tube Earpiece, 2.5mm Straight Single Pin for WP300 Bluetooth Control Pod
<b>RLN6242</b>	Low Noise Kit with Translucent Tube and 1 Clear Rubber Eartip
<b>5080384F72</b>	Replacement Foam Plugs for RLN6242. Noise Reduction = 24 dB. Pack of 50 Pairs
<b>RLN6282</b>	Replacement Standard Clear Rubber Eartip for RLN6242, Pack of 50

## POWER ACCESSORIES

<b>PS000150A31</b>	USB-A Wall Charger, 5V/1.5A, 240VAC (NA/Japan Plug) <sup>5</sup>
<b>PS000150A32</b>	USB-A Wall Charger, 5V/1.5A, 240VAC (Euro Plug) <sup>5</sup>
<b>PMKN4294</b>	USB-C to USB-A Cable
<b>HKLN4690</b>	TLK 110 Battery Cover

## CARRY ACCESSORIES

<b>PMLN8439</b>	Swivel Carry Holster
<b>PMLN6074</b>	Nylon Wrist Strap for Securely Carrying Motorola Two-Way Radios

## ANTENNAS

<b>HKAN4005</b>	NA Stubby Antenna
-----------------	-------------------

<sup>5</sup> USB cable for wall adapters sold separately



Call: (844) 917-4215  
Email: [info@callmc.com](mailto:info@callmc.com)  
Web: [www.callmc.com](http://www.callmc.com)



Motorola Solutions, Inc. 500 West Monroe Street, Chicago, IL 60661 U.S.A. [motorolasolutions.com](http://motorolasolutions.com)

MOTOROLA, MOTOTRBO, MOTOROLA SOLUTIONS and the Stylised M Logo are trademarks or registered trademarks of Motorola Trademark Holdings, LLC and are used under license. All other trademarks are the property of their respective owners. © 2023 Motorola Solutions, Inc. All rights reserved. 09-2023