

Compact Series Routers

RX55 Product Description

The AirLink® RX55 is optimized for Industrial IoT with ultra-low power consumption and a rugged design for extreme conditions. With advanced networking and industry-standard container support capabilities, the RX55 delivers intelligence securely at the edge for mission-critical applications on both public and private networks.

Ideal Applications

Reliable connectivity for fixed and mobile assets in:

- Utilities
- Oil & Gas
- Public Safety
- Agriculture

- Environmental monitoring
- Critical Infrastructure
- Smart Cities

Benefits

- Compact size makes installation easier
- Ultra-low power consumption makes it ideal for solar or battery-powered applications
- Connect to a wide variety of devices from video to low-power IoT
- Remote device management through AirLink Complete
- Ready for your edge computing workloads (Beta)

Compact, Rugged, Low power, LTE **Router for Industrial** IoT, SCADA and fleet applications in private and public networks.

MTEC

KEY FEATURES

- 4G LTE-A
- Dual 1x1 Wi-Fi 5
- 1 Gigabit Ethernet
- Single/Dual Serial
- GNSS
- IP64 Rated
- AirLink OS with AirLink Complete





RX55 Services and Support

AIRLINK COMPLETE

Maximize your AirLink RX55 hardware investment with AirLink Complete – a comprehensive service package designed to empower you with the tools and support necessary to secure, optimize and effortlessly scale your RX55 deployments.

AirLink Complete includes*:

- AirLink Management Service (ALMS) for remote device and security management
- Expert technical support
- Extended hardware warranty up to 5 years maximum
- For more information on AirLink Complete visit our *web page*

*With active subscription. 1-year subscription included with the RX55 purchase

AIRLINK PREMIUM

Ideal for organizations managing mission-critical vehicle fleets, this service upgrade encompasses all the benefits of <u>AirLink Complete</u>*, enhanced with:

- Advanced Mobility Reporting*: Offers comprehensive coverage and fleet reporting to monitor your network and vehicles.
- Advance Replacement*: Provides same-day shipping for in-warranty router replacements, minimizing downtime, spare inventory and keeping your operations running smoothly.

*With active subscription.

HYBRID CLOUD

This optional feature merges the benefits of cloud technology with on-premise security controls for the management of your AirLink XR and RX routers, offering ultimate security and control.

Hybrid Cloud is available to add to an active AirLink Complete or Premium subscription.

AIRLINK CONNECTION MANAGER (ACM) - MOBILE VPN

This purpose-built VPN solution securely extends your enterprise network to your AirLink router and its connected devices and applications.

Optimized for use in a mobile, multi-network environment, it seamlessly maintains VPN tunnels as users roam between multiple carrier and Wi-Fi networks to prevent downtime and loss of communications.

Available in a FIPS 140-2 compliant offering.

ANTENNAS

- Tested and certified to provide guaranteed performance with all AirLink routers
- Accelerate deployment with always-on, end-to-end connectivity
- For more information on antennas specific to the RX55 router visit our *web page*









AirLink RX55 – Router Specifications

KEY FEATURES		
Cellular Radios	4G LTE-A	
Wi-Fi	Dual 1x1 Wi-Fi 5	
Ethernet	1x Gigabit Ethernet Port (RJ45)	
Serial	Dual RS-232 serial port (DB9) - Base Model (with optional Y-cable) Single RS-232 serial port (DB9) - Wi-Fi & Wi-Fi Plus Model	
GNSS	30 Channel GNSS	
CAN	Wi-Fi & Wi-Fi Plus Model (with optional Y-cable)	
1/0	1 GPIO	
USB	USB 2.0 Micro-B	
IP Rating	Sealed Aluminum Housing (IP64)	
Services	AirLink Complete	
Operating System	AirLink OS	
Management System	ALMS	

	NAM	EMEA-APAC
CELLULAR		
Technology	4G LTE-A	4G LTE-A
Cellular	4G, 3G	4G, 3G
Peak Downlink (Theoretical)	300 Mbps	300 Mbps
Peak Uplink (Theoretical)	150 Mbps	150 Mbps
LTE Category	Cat-7	Cat-7
Region	NAM	EMEA, APAC
Radio	EM7411	EM7421
MIMO	2x2	2x2
RF Connectors	SMA	SMA
SIM	Dual SIM (Mini-2FF)	Dual SIM (Mini-2FF)



	NAM		EMEA-AP	AC
FREQUENCY BANDS				
	4G LTE	3G (HSPA+)	4G LTE	3G (HSPA+)
1			B1	B1
2	B2	B2		
3			B3	
4	B4	B4		
5	B5	B5		B5
7	B7		B7	
8			B8	B8
12	B12			
13	B13			
14	B14			
20			B20	
25	B25			
26	B26			
28			B28	
32			B32	
38			B38	
40			B40	
41	B41		B41	
42	B42		B42	
43	B43		B43	
48	B48			
66	B66			
71	B71			

	NAM	EMEA-APAC	
WIRELESS CERTIFICATION			
Regulatory	FCC, IC/ISED, PTCRB	GCF, CE, RED, RCM	
Carrier	Verizon, AT&T, T-Mobile, Bell, CBRS		
Public Safety	FirstNet®		
Part Numbers	1104927 Base	1104929 Base	
	1104928 Wi-Fi	1104930 Wi-Fi	
	1104934 Wi-Fi Plus	1104933 Wi-Fi Plus	

WI-FI (Optional)	
Wi-Fi Standard	Wi-Fi 5
Access Point	Dual
Client (Depot/WAN)	Yes
Client & AP	Yes
Peak Throughput (Theoretical)	433 Mbps
МІМО	Dual 1x1
Security	WPA2 Enterprise
Clients	10 per radio
SSID	1 per radio
Output Power	16 dBm
Frequency	2.4/5 GHz
RF Connectors	SMA (Reverse Polarity)
ENVIRONMENTAL	
Operating Temperature	-40°C to +70°C / -40°F to +158°F -30°C to +70°C / -22°F to +158°F (Wi-Fi variant)
Storage Temperature	-40°C to +85°C / -40°F to +185°F
Humidity	95% RH @ 60°C
Military Specification	MIL-STD-810G (shock, vibration, thermal shock, humidity)
IP Rating	IP64

INDUSTRY CERTIF	INDUSTRY CERTIFICATIONS		
Safety	IECEE Certification Bodies Scheme (CB Scheme)		
Vehicle Usage	E-Mark (UN ECE Regulation 10.04), ISO7637-2, SAE J1455 (Shock, Vibration, Electrical)		
Environmental Directives	RoHS2, REACH, WEEE, Prop 65		
Hazardous Environments	Class 1 Div 2 – Ambient temperatures of -30°C to +60°C IECEx & ATEX		
Rail Usage	North America: EN50155 EMEA & APAC: EN50155/EN45545 (Rolling Stock)		
POWER			
Input Voltage	7 to 36 VDC		
Power Consumption	LTE Idle Power: 717mW (75 mA @ 12VDC) Standby Mode Power: 38mW (4.4 mA @ 12 VDC) triggered on low voltage, I/O or periodic timer		
Power Modes	Low voltage disconnect to prevent battery drain Built-in protection against voltage transients including 5 VDC engine cranking and +200 VDC load dump Ignition Sense with time delay shutdown Configurable features and ports to optimize power consumption		
SECURITY			
AAA	802.1x /Radius authentication with Wi-Fi and Ethernet		
Firewall	Stateful firewall with port forwarding, DMZ		
	WPA2/WPA3 Personal/Enterprise		
WLAN Encryption	WFA2/WFA3 Felsonal/Enterprise		



NETWORK AND ROUTING			
	Semtech Cognitive Wireless	Support	
	IPv4 and IPv6 Routing	Llandurana	
	Network Address Translation (NAT)	Hardware	
	Port Forwarding	Warranty	
	DHCP Server		
	IP Passthrough	Device	
	LAN Segmentation	Managemen	
	IPv4 Passthrough and IPv6 Prefix Extension		
	WAN/LAN Connection Policy Management	Software Up	
	Policy-Based Routing		
	Configurable MTU size		
	Static Routing	AIRLINK PR	
	WAN Ethernet	Includes All /	
QoS	Application/Traffic Priority Queuing	Advanced M	
WAN Monitors	Connection Failure Recovery	Reporting	
	· · ·	Advance	
VPN		Replacemen	
	Integrated with ACM VPN Server	RELIABILITY	
	IPsec protocol with IKEv1/IKEv2		
	FIPS 140-2 Level 1 compliant	MTBF	
Encryption	AES128/AES192/AES256	_	
Hashing	SHA256/SHA384/SHA512	-	
Key Exchange	DHGroup14/15/16/17/18/19/20/21	ACCESSORI	
	LAN to LAN and Host to LAN	In The Devi	
	Up to 10 concurrent tunnels per link	In The Box	
	MOBIKE protocol		
	IP compression	Other Access	
	Full/Split Tunnel	(sold separa	
	Dead Peer Detection (DPD)	(
ROUTER MANAGE	EMENT INTERFACES		
	ALMS	DIMENSION	
	Local web user interface		
	REST API (Beta)	Size	
EDGE COMPUTIN	G		
	Support for Edge Compute Containerized Applications	Weight	
	Support for Edge Compute Containerized Applications (Beta)		
DAM12		*With current AirLi	
RAM ^{1,2}	50 MB (Base & Wi-Fi)	**Full warranty ter	
	200 MB (Wi-Fi Plus)	***With current Air	
Storage (Flash) ¹	200 MB (Base & Wi-Fi)		
-	2.8 GB (Wi-Fi Dluc)		

AIRLINK COMPLETE (1 Year Included With Router Purchase)			
Support	24/7 technical support*		
Hardware Warranty	1-year standard hardware warranty Extended hardware warranty up to 5 years with current subscription**		
Device Management	AirLink Management Service (ALMS)*		
Software Updates	Unrestricted critical firmware updates through at least December 31st, 2029		
AIRLINK PREMIUM (Optional Upgrade) Includes All Airlink Complete Features* and Adds:			
Advanced Mobility Reporting	Coverage and fleet reporting***		
Advance Replacement	Same-day shipping for in-warranty router replacements***		
RELIABILITY			
MTBF	>100 years • Ground Benign, 25°C • MTBF calculations performed per Telcordia "Reliability Prediction Procedure for Electronic Equipment" document number SR-332, Method I, Issue 3		
ACCESSORIES			
In The Box	RX55, DC Power Cable and Quick Start Guide, AirLink Complete Leaflet		
Other Accessories (sold separately)	2000579 AC Adapter, 12VDC 6000659 DIN Rail Bracket 6001238 Dual Serial Y-cable 6001479 Serial CAN Y-cable For Antenna options visit: <u>web page</u>		
DIMENSIONS			
Size	119 mm x 33 mm x 85 mm (102 mm including Wi-Fi connectors) 4.69 in x 1.34 in x 3.35 in (3.70 in including connectors)		
Weight	320 g / 0.7 lb		

*With current AirLink Complete subscription

**Full warranty terms are available at <u>www.sierrawireless.com/end-user-warranty</u>

***With current AirLink Premium subscription

1. Approximation available to containers (not device total)


2. Depends on other enabled features


CPU


2.8 GB (Wi-Fi Plus)

Dual Core ARMv7 32-bit

AirLink RX55 - Router Dimensions Diagram







Contact MCA

Cellular Networking Solutions (CNS) Team



- 888.550.8728
- cnsinfo@callmc.com
- 🗔 https://lte.callmc.com

About Semtech

Semtech Corporation (Nasdaq: SMTC) is a high-performance semiconductor, IoT systems and cloud connectivity service provider dedicated to delivering high-quality technology solutions that enable a smarter, more connected and sustainable planet. Our global teams are committed to empowering solution architects and application developers to develop breakthrough products for the infrastructure, industrial and consumer markets.

To learn more about Semtech technology, visit us at Semtech.com or follow us on LinkedIn or X.



"Semtech", "Sierra Wireless" and "AirLink" are registered trademarks of Semtech Corporation or its subsidiaries. Other product or service names mentioned herein may be the trademarks of their respective owners. © 2022 Sierra Wireless, Inc. © 2023 Semtech Corporation. All rights reserved. 2024.06.07