

# DTR600

## RELIABLE DIGITAL COMMUNICATIONS

THE ABILITY TO COMMUNICATE AND SOLVE PROBLEMS IN REAL TIME IS CRITICAL TO ENSURING SEAMLESS AND EFFICIENT BUSINESS OPERATIONS.

With Motorola Solutions' license free DTR600 Series radios, digital on-site communication is easier and more reliable than ever. Your team can communicate quickly, solve problems rapidly and address unexpected situations – ultimately improving operational efficiency and customer satisfaction. Motorola Solutions' DTR Series radios are the perfect partner for your business – delivering all the benefits of reliable digital communications and interference free, private communications.

### FEATURES

- 900MHz license free radios
- Wide area coverage
- Flexible call options
- Scan
- Over the air contact cloning
- Rental timer
- Quick text
- Call alert
- Loud and clear audio



DTR600



# KEY FEATURES



## SLIM, RUGGED DESIGN

Compact and IP54 rated. A durable design meets U.S. Military 810G standards for shock, vibration, water, dust and temperature extremes - so it will operate in the harshest working conditions.



## VIBRANT COLOR DISPLAY

A full-graphic, backlit display uses brightness adjustment to provide a crisp and clear image, while an intuitive navigation menu helps you quickly and easily locate all radio features.



## CALL ALERT

Send a signal to another radio before you call to ensure the receiver is aware of the call request.



## PROMINENT FUNCTIONAL KEYS

Programmable button can be used to quickly access call features like Call All/Page All, to talk to radios without searching through your channel list.



## ANTIMICROBIAL HOUSING PROPERTIES

The radio housing contains built-in antimicrobial properties that prevent growth of mold and germs\* resulting in stain-resistant and orderless devices.

\*The antimicrobial properties do not protect users or others against bacteria, viruses, germs, or other disease organisms. Always clean this product thoroughly before and after each use. Does not apply to accessories.



## LICENSE FREE, HASSLE FREE

Designed for business operations, the DTR Series radio will free your time from regulatory paperwork and licensing applications and saving radio licensing fees.

## TAKE COVERAGE AND CLARITY FURTHER

Your team will enjoy expanded in-building coverage – up to 350,000 sq. ft. (or 30 floors indoors) with the standard whip antenna. Digital audio quality stays loud and clear – up to the edge of coverage – without static or dead zones.

## INTERFERENCE FREE, PRIVATE COMMUNICATIONS

Take advantage of private communications and quickly set up for radio fleet with a unique Radio Profile ID Number. By choosing from 10,000 available codes, you can assure privacy from other neighboring radios.

Leverage Frequency Hopping Spread Spectrum (FHSS) technology for more reliable and private communication when compared to standard analog radios.

## FLEXIBLE CALL OPTIONS

With up to 200 entries for individual private contacts, private groups and public groups your team can handle the unique needs of different business operations.

**Digital One-to-One Private Calling** allows private communications with a specific user to free the radio channel from unnecessary back and forth chatter. The recipient receives an alert – either audible or vibrating – and their radio displays the caller ID.

**Digital One-to-Many Group Calling** enables public group calls. All other DTR Series radios on the same group ID and channel can hear communications.

# THE PERFECT PARTNER FOR BUSINESS COMMUNICATION



## Retail Stores

Easily locate a clerk to check stock and coordinate restocking operations.

## Education

Keep teachers, administrators, crossing guards and maintenance crews in touch so they can respond quickly – preventing small problems from escalating into bigger problems. Facilitate and manage school events and activities efficiently and keep everyone safe by enabling constant communication among staff members.

## Restaurants

Ensure tables are ready quickly and customers enjoy their dining experience by seamlessly communicating with restaurant staff.

## Hospitality

Keep your staff connected - from the front desk concierge, to event planners and maintenance personnel. This means faster response to guest requests, at special events and emergencies resulting in overall better customer satisfaction.

| GENERAL SPECIFICATIONS |  | DTR600                                                                                                                                                           |
|------------------------|--|------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Channels               |  | 30                                                                                                                                                               |
| Frequency              |  | 900 MHz ISM FHSS                                                                                                                                                 |
| Range coverage         |  | 350k sq ft 30 floors <sup>1</sup>                                                                                                                                |
| License Free Band      |  | Licensed by the Federal Communications Commission (FCC) and Industry Canada to operate in the license-free 900 MHz ISM (Industrial, Scientific and Medical) band |
| Dimensions             |  | 5.06" H x 2.2" W x 1.06" D<br>(128.5mm H x 56mm W x 27mm D)                                                                                                      |
| Weight                 |  | 7.87oz. (223 g)                                                                                                                                                  |

| ENERGY SPECIFICATIONS |                       |
|-----------------------|-----------------------|
| Battery               | 3.7V ± 0.5V           |
| Battery Life          | 16.5 hrs <sup>2</sup> |

| ENVIRONMENTAL SPECIFICATIONS |                                     |
|------------------------------|-------------------------------------|
| Operating Temperature        | -30°C to +60°C (Radio) <sup>3</sup> |
| Storage Temperature          | -40°C to +85°C (Radio) <sup>3</sup> |
| Dust and Water Intrusion     | IEC 60529 IP54                      |

| TRANSMITTER SPECIFICATIONS          |                         |
|-------------------------------------|-------------------------|
| RF Output                           | 1W                      |
| Channel Spacing                     | 50kHz                   |
| Frequency Stability (-30°C to 60°C) | ± 1PPM                  |
| TX Spurious Emissions - radiated    | <54dBuV/m (3m)          |
| Audio Distortion                    | <3%                     |
| TX ACPR                             | -50dBc                  |
| FCC Modulation                      | 8-level FSK 900MHz FHSS |

| RECEIVER SPECIFICATIONS               |                  |
|---------------------------------------|------------------|
| Preamble Sensitivity                  | -125dBm          |
| Frequency Stability (-30°C to +60°C)  | ± 1PPM           |
| RX Spur Emissions - radiated          | <43.5dBuV/m (3m) |
| Blocking Immunity: ±500 kHz to ±1 MHz | 75dB             |
| Blocking Immunity: ±1 MHz to ±15 MHz  | 80dB             |
| Audio Output @ <5% distortion         | 1W               |

|                   | MIL-STD 810C |               | MIL-STD 810D |              | MIL-STD 810E |              | MIL-STD 810F |               | MIL-STD 810G |             |
|-------------------|--------------|---------------|--------------|--------------|--------------|--------------|--------------|---------------|--------------|-------------|
|                   | METHOD       | PROCEDURE     | METHOD       | PROCEDURE    | METHOD       | PROCEDURE    | METHOD       | PROCEDURE     | METHOD       | PROCEDURE   |
| Low Pressure      | 500.1        | I             | 500.2        | II           | 500.3        | II           | 500.4        | II            | 500.6        | II          |
| High Temperature  | 501.1        | I, II         | 501.2        | I/A1, II/A1  | 501.3        | I/A1, II/A1  | 501.4        | I/Hot, II/Hot | 501.6        | I/A1, II/A1 |
| Low Temperature   | 502.1        | I             | 502.2        | I/C3, II/C1  | 502.3        | I/C3, II/C1  | 502.4        | I/C3, II/C1   | 502.6        | I/C3, II/C1 |
| Temperature Shock | 503.1        | I             | 503.2        | A1/C3        | 503.3        | A1/C3        | 503.4        | I             | 503.6        | I-C         |
| Solar Radiation   | 505.1        | II            | 505.2        | I/Hot-Dry    | 505.3        | I/Hot-Dry    | 505.4        | I/Hot-Dry     | 505.6        | I/A1        |
| Rain              | 506.1        | I, II         | 506.2        | I, II        | 506.3        | I, II        | 506.4        | I, III        | 506.6        | I, III      |
| Humidity          | 507.1        | II            | 507.2        | II/hot-humid | 507.3        | II/hot-humid | 507.4        | -             | 507.6        | II/Agg      |
| Salt Fog          | 509.1        | I             | 509.2        | I            | 509.3        | I            | 509.4        | -             | 509.6        | -           |
| Dust              | 510.1        | I, II         | 510.2        | I, II        | 510.3        | I, II        | 510.4        | I, II         | 510.6        | I, II       |
| Vibration         | 514.2        | VIII/F, W, XI | 514.3        | I/10, II/3   | 514.4        | I/24, II/5   | 514.5        | I/24, II/5    | 514.7        | I/24, II/5  |
| Shock             | 516.2        | I, II         | 516.3        | I, IV        | 516.4        | I, IV        | 516.5        | I, IV         | 516.7        | I, IV       |

DTR radios meet test methods from Military Standards 810, C,D,E,F and G including shock, vibration, extreme temperatures and dust. DTR radios also satisfy environmental and energy efficiency certifications (CE/CEC, ROHS and WEEE).

1: Coverage depends on terrain and environmental conditions.

2: Typical battery life, 5/5/90 profile at maximum transmitter power. Actual observed runtimes may vary.

3: Radio only. Battery specifications may be different.

Specifications subject to change without notice. All specifications shown are typical values

# DTR SERIES ACCESSORIES



HKLN4601



HKLN4604



HKLN4599



PMLN7939

## AUDIO ACCESSORIES

Comfortable and extended wear, these audio accessories provide prominent push-to-talk features and hands free communication.

|          |                                                          |
|----------|----------------------------------------------------------|
| HKLN4599 | Earpiece with in-line microphone and push-to-talk        |
| HKLN4601 | Surveillance with in-line microphone and push-to-talk    |
| HKLN4604 | Swivel Earpiece with in-line microphone and push-to-talk |



PMAF4024



PMAF4025

## ANTENNAS

Choose between two antenna options to compliment your work environment.

|          |                                    |
|----------|------------------------------------|
| PMAF4024 | 900MHz (902-928MHz) Whip Antenna   |
| PMAF4025 | 900MHz (902-928MHz) Stubby Antenna |

## CARRY ACCESSORIES

Wear the radio on your belt so you can be hands free.

|          |                     |
|----------|---------------------|
| PMLN7939 | Swivel Clip Holster |
|----------|---------------------|



PMNN4578



PMPN4468



PMPN4465

## BATTERIES, CHARGERS AND CABLES

Keep your radios functioning at all times with these energy essentials. Charge your Lithium Ion batteries in single or multi-charging docks.

|             |                                                  |
|-------------|--------------------------------------------------|
| PMPN4465    | 6-Pocket Multi Unit Charger Kit                  |
| PMPN4468    | Single Unit Charger (Tray Only)                  |
| PMPN4469    | Single Unit Charger Kit (Tray + 3W Power Supply) |
| PMNN4578    | Li-ion 2500 mAh, 3.7v Battery                    |
| HKKN4027    | Business Radio Programming CPS Cable             |
| HKKN4028    | Business Radio Cloning Cable                     |
| PS000228A01 | 3W Power Supply                                  |
| PS000227A11 | 5W Quick Charge Power Supply                     |



Call: (844) 917-4215  
Email: info@callmc.com  
Web: www.callmc.com

Motorola Solutions, Inc. 500 West Monroe Street, Chicago, IL 60661 U.S.A. [motorolasolutions.com](http://motorolasolutions.com)

MOTOROLA, MOTO, MOTOROLA SOLUTIONS and the Stylized M Logo are trademarks or registered trademarks of Motorola Trademark Holdings, LLC and are used under license. All other trademarks are the property of their respective owners. © 2019 Motorola Solutions, Inc. All rights reserved. 08-2019