

HAY TEDDERS PULL-TYPE

Save More Time TURN MORE HAY

IronCraft Hay Tedders are built for efficient forage distribution, helping you achieve faster and more even drying. With independent rotors that adapt to varying ground conditions and adjustable working angles, these tedders maximize performance in any field. Available in four working widths and designed for easy transport, they deliver reliability and simplicity for operations of all sizes.



HAY TEDDERS

PRODUCT HIGHLIGHTS



RECOMMENDED FOR 20-60 PTO Horsepower tractors



GROUND ADAPATION THROUGH INDEPENDENT ROTORS WITH ARTICULATED FRAME SECTIONS AND LARGE DIAMETER WHEELS



IronCraft tedders are equipped with independent rotors that can easily adapt to various ground conditions. They are available in 4 different working widths and come with a pull-type hitch. Depending on the model, the working angle can be adjusted either hydraulically or mechanically. These tedders are designed to be user-friendly and easy to transport, ensuring efficient forage distribution for quick and uniform drying.





	T210	T417	T419	T624
MINIMUM HP REQUIRED	20 HP	50 HP	50 HP	50–60 HP
WORKING WIDTH	10.2'	17'	19'	24'
TRANSPORT WIDTH	10.5'	9.8'	10.5'	9.8'
TRANSPORT HEIGHT	3.6'	8.7'	9.4'	12.1'
TRANSPORT LENGTH	7.5'	9'	9.5'	9'
NUMBER OF ROTORS	2	4	4	6
TINE ARMS PER ROTOR	6	6	6	6
ROTOR TIRE	2 x 15 x 6.0-6	4 x 16 x 6.5-8	2 x 16 x 6.5-8 2 x 18.5 x 8.5-8	8 x 16 x 6.5-8 (Walking Tandem Center Wheels)
WEIGHT	425 LBS	1,080 LBS	1,157 LBS	1,740 LBS
ROAD SIGNALING KIT	N/A	N/A	N/A	Standard
WORKING ANGLE ADJUSTMENT	Mechanical	Mechanical (Optional Hydraulic Kit)	Hydraulic	Hydraulic
WING FOLD	Fixed	Hydraulic	Hydraulic	Hydraulic
REAR REMOTES REQUIRED	1	1 (2 w/ Opt. Hyd. Kit)	2	2