



3520 SERIES

20' FLEX-WING CUTTER



Take on the toughest jobs
20 FEET AT A TIME

Whether you're maintaining utility right-of-way, airports, fields, or trail systems - the 3520 will be your trusted sidekick. Built for the toughest conditions, the 3520 provides a cleaner, more reliable cut while being easy to maintain and service.

3520 SERIES

20' FLEX-WING CUTTER

WATCH IT
IN ACTION



PRODUCT HIGHLIGHTS

Made in the U.S.A.
WITH U.S. & IMPORTED PARTS



OPTIONAL WALKING TANDEM



HYDRAULIC TAILWHEEL
ASSEMBLIES & SPRING-
LOADED SUSPENSION SYSTEM



ADDITIONAL WING DEBRIS GUIDE
FOR IMPROVED MATERIAL VELOCITY
AND DECK RIGIDITY

20' CUTTING
WIDTH



FLAT TOP DESIGN FOR EASY
CLEANING & MAINTENANCE



REPLACEABLE, HEAVY-DUTY
SKID SHOES

AVAILABLE
COLORS:



	3520
RPM	540 or 1000
HP REQUIRED	80 minimum PTO
WORKING WIDTH	240"
OVERALL WIDTH	249"
TRANSPORT WIDTH	94" (with tandems 108")
TONGUE WEIGHT	2,700 lbs
WEIGHT	8,700 lbs w/ 8- 26" Laminated Tires
CUTTING HEIGHT	2" to 15"
CUTTING CAPACITY	4"
DECK THICKNESS	10 GA Center Deck / 7 GA Wing Decks
SIDE BANDS	1/4" x 13-1/2"
SUSPENSION	2 Heavy Duty Springs in Center Tailwheel Assembly & 1 Heavy Duty Spring on each Wing Tailwheel Assembly
SKID SHOES	Replaceable
PTO DRIVE SHAFT	ASAE CAT 6
WING DRIVE PTO	ASAE CAT 6
DRIVELINE PROTECTION	Slip Clutch
BLADE HOLDER	Round Pan
GEARBOX RATING	275 HP

OUTBOARD GEARBOX RATING	225 HP
WING FLEX	22 Degrees Down to 100 Degrees Up
BLADES	1/2" x 4" Uplift
HITCH TYPE	Swivel Pivot Self Leveling
GEARBOX WARRANTY	5 year limited
DECK RINGS	Standard
SAFETY TOW CHAIN	Standard
GUARDING OPTIONS	Single Row Chains Standard
WHEEL TYPE	26" Laminated, 26" Foam Filled, or 29" Pneumatic
BLADE TIP SPEED	540 RPM 16,600 FPM / 1,000 RPM 17,400 FPM



(423) 405-5150

IRONCRAFTUSA.COM

Version 2.7.24