



SICKLE BAR MOWER


The skid steer or excavator mounted Sickle Mower allows operators to increase productivity of berm cutting and trail maintenance jobs with its large cut width. A great attachment for farms, orchards, or road maintenance businesses.

These Sickle Mowers can cut below 45 degrees flush to the ground and up to 110 degrees allowing for ditch cutting and roadside branch or hedge trimming. The frame is made of 3" square tubing and features a breakaway bar to protect the unit



SKID STEER

| | |
|------------------|---------------------------------------|
| AQUATIC APPROVED | No |
| CUTTER LENGTH | 7' or 9' |
| CUTTING ANGLE | 110° to -45° |
| CUTTING CAPACITY | 2" Material |
| DRIVE SYSTEM | Gerotor Motor w/ Planetary Gear drive |
| ELECTRICAL | 12V Switched Solenoid |
| FLOW RANGE | 15-20 GPM |
| MAX PRESSURE | 3,500 PSI |
| NUMBER OF TEETH | 28 for 7' - 36 for 9' |
| TOOTH STYLE | Top Serrated 2" Segment |
| WEIGHT | 780 lb for 7' - 950 lbs. for 9' |



| | 5 FT EXCAVATOR | 7 FT EXCAVATOR | 9 FT EXCAVATOR |
|------------------|--------------------------------|--------------------------------------|--------------------------------------|
| AQUATIC APPROVED | Yes | No | No |
| CUTTER LENGTH | 5 ft. | 7 ft. | 9 ft. |
| CUTTING CAPACITY | 2" Material | 2" Material | 2" Material |
| DRIVE SYSTEM | Gerotor Motor w/Pitman drive | Gerotor Motor w/Planetary Gear drive | Gerotor Motor w/Planetary Gear drive |
| FLOW RANGES | 9-12 GPM, 12-15 GPM, 15-20 GPM | 12-15 GPM, 15-20 GPM | 12-15 GPM, 15-20 GPM |
| MAX PRESSURE | 3,500 PSI | 3,500 PSI | 3,500 PSI |
| NUMBER OF TEETH | 22 | 28 | 36 |
| TOOTH STYLE | Top Serrated 2" Segment | Top Serrated 2 Segment" | Top Serrated 2 Segment" |
| WEIGHT | 225 lbs. (Without Mount) | 350 lbs. (Without Mount) | 400 lbs. (Without Mount) |