Hydrogen Sulfide Test Kit HS-C (2537800)


DOC326 98 00022


Test preparation

CAUTION: A Review the Safety Data Sheets (MSDS/SDS) for the chemicals that are used. Use the recommended personal protective equipment.

- · Analyze the samples immediately. The hydrogen sulfide concentration decreases quickly after the sample is collected.
- Rinse the bottle with sample before the test. Rinse the bottle with deionized water after the test. ٠
- Wash all labware between tests. Contamination can change the test result. Clean with a nonabrasive detergent or a solvent such as isopropyl alcohol. Rinse with deionized water. Wipe and dry with a soft cloth.
- The test paper is light blue. Small variations in the test paper color do not have an effect on test accuracy.

Test procedure—Hydrogen Sulfide (0–5 mg/L H₂S)





1. Fill the bottle to the 100-mL mark with sample.

2. Put one 3. Add two 1-q spoons of Citric Hydrogen Sulfide Test Paper into the Acid to a piece of bottle cap. Do not weighing paper. get the paper wet.

4. Use a different spoon to add two 1-g spoons of Sodium Bicarbonate to the same piece of

weighing paper.

5. Add all of the powder to the sample in the bottle.



6. Immediately the bottle.



7. Start a tighten the cap on 2-minute timer.

8. Carefully swirl the bottle. Do not get the cap wet.



again when the

not get the cap

wet.



10. When the timer expires, reaction slows. Do remove the test paper from the cap. Compare the color on the test paper to the colors on the test chart to aet the result in mg/L.

9. Swirl the bottle

Replacement items

Description	Unit	Item no.
Citric Acid	105 g	7067105
Sodium Bicarbonate	105 g	776105
Spoon, measuring, 1.0 g	each	51000
Hydrogen sulfide bottle, with cap	each	2532800
Hydrogen Sulfide Test Chart	each	2537900
Hydrogen Sulfide Test Paper	100/pkg	2537733

Optional items

Description	Unit	Item no.
Water, deionized	500 mL	27249
Weighing paper, 102 x 102 mm	500/pkg	1473885