



ELASTOMERIC FIRESTOP SEALANT FOR CONSTRUCTION JOINTS

# SpecSeal® ES Elastomeric Firestop Sealant

SpecSeal® ES Sealant is a latex-based gun grade elastomeric firestop sealant designed for construction joint applications. Once cured, ES Sealant forms a flexible shield against the passage fire and smoke. In dynamic joint conditions, ES Sealant is tested to accommodate up to 25% compression/extension of the installed joint width.

## Features & Benefits

- Highly elastomeric gun grade sealant
- Tested for up to 4 Hour fire resistance rating when tested to ASTM E1966/UL 2079
- Paintable
- Listed in over 45 UL® Certified Construction Joint Systems



## ORDERING INFORMATION

Catalog Number	UPC Number	Description	(UOM) Qty.	Case Qty.	Weight (Each)
ES105	730573081051	5 Gal. Pail (19.0 liters) 1,155 cu.in.	1	N/A	63.30 lbs (28.71 kg)
ES105BR	730573952054	5 Gal. Pail (19.0 liters) 1,155 cu.in. - Brick Red	1	N/A	63.30 lbs (28.71 kg)
ES105GL	730573081143	5 Gal. Pail (19.0 liters) 1,155 cu.in. - Light Grey	1	N/A	63.30 lbs (28.71 kg)
ES120	730573081037	20 oz. Sausage (592 ml) 36 cu. in.	1	12	1.97 lbs (0.89 kg)
ES120BR	730573952061	20 oz. Sausage (592 ml) 36 cu. in. - Brick Red	1	12	1.97 lbs (0.89 kg)
ES129	730573081297	29 oz. Tube (858 ml) 52 cu. in.	1	10	3.05 lbs (1.38 kg)
ES129BR	730573952078	29 oz. Tube (858 ml) 52 cu. in. - Brick Red	1	10	3.05 lbs (1.38 kg)



TEST STANDARDS: ASTM E1966 (UL2079), CAN/ULC-S115

Pale Blue Color

Brick Red Color

Light Grey Color

Permanent Solution



Click or scan to learn more

