

SpecSeal® 8 Inch Cast-In Firestop Device


The SpecSeal® 8 Inch Cast-In Device (CID) provides a robust yet simple integrated firestop system. With fewer components and welded construction, the 8" CID from Specified Technologies Inc. is designed to ease casting with its flat, simple shape that reduces defects and stress points.

Features & Benefits


- Smooth surface design allows concrete to flow around the device, properly filling in corners and gaps
- Works with metallic and non-metallic penetrants
- Includes a removable form for a clean, ready-to-use opening
- Robust construction for long-term durability
- Bi-directional, allowing for use in both floor and ceiling assemblies
- Eliminates the need to core drill and firestop
- Manufactured in the USA in an ISO-certified facility

Applications

- 8-inch trade size plastic, metallic, and insulated metallic pipes
- Accommodates 6 in (152 mm), 8 in (203 mm), 10 in (254 mm), 12 in (305 mm), and 14 in (356 mm) concrete depths



Cast-In Device
for plastic pipes



Cast-In Device
for metallic pipes

PHYSICAL PROPERTIES (AS SUPPLIED)

VALUE

Housing Construction	Zinc-plated, Cold Rolled Steel (SECC)
Expansion Begins	320°F (160°C)
Volume Expansion	30x to 60x
In Service Temperature	Max. 130°F (54°C)
Shelf Life	No Limit
Standard Device Footprint	16.25 in (413.8 mm)

PERFORMANCE

Tested to ASTM E814, CAN/ULC- S115, and ASTM D4833

SpecSeal®

CID

DEVICES FOR COMBUSTIBLE AND NON-COMBUSTIBLE PENETRANTS

SpecSeal® 8 Inch Cast-In Firestop Device



ORDERING INFORMATION (DEVICES FOR COMBUSTIBLE PENETRANTS)

Catalog Number	UPC Number	Description	Pipe Trade Size	Concrete Thickness	(UOM) Qty.	Case Qty.	Weight (Each)
CD801P	730573343463	6 in (152 mm) Height	8 in (203 mm)	6 in (152 mm)	1	1	10.9 lbs (4.94 kg)
CD802P	730573343494	8 in (203 mm) Height	8 in (203 mm)	8 in (203 mm)	1	1	11.0 lbs (4.99 kg)
CD803P	730573343500	10 in (254 mm) Height	8 in (203 mm)	10 in (254 mm)	1	1	11.1 lbs (5.03 kg)
CD804P	730573343517	12 in (305 mm) Height	8 in (203 mm)	12 in (305 mm)	1	1	11.2 lbs (5.08 kg)
CD805P	730573343524	14 in (356 mm) Height	8 in (203 mm)	14 in (356 mm)	1	1	11.3 lbs (5.13 kg)

ORDERING INFORMATION (DEVICES FOR NONCOMBUSTIBLE PENETRANTS)

Catalog Number	UPC Number	Description	Pipe Trade Size	Concrete Thickness	(UOM) Qty.	Case Qty.	Weight (Each)
CD801M	730573343548	6 in (152 mm) Height	8 in (203 mm)	6 in (152 mm)	1	1	6.4 lbs (2.90 kg)
CD802M	730573343555	8 in (203 mm) Height	8 in (203 mm)	8 in (203 mm)	1	1	6.5 lbs (2.95 kg)
CD803M	730573343562	10 in (254 mm) Height	8 in (203 mm)	10 in (254 mm)	1	1	6.6 lbs (2.99 kg)
CD804M	730573343579	12 in (305 mm) Height	8 in (203 mm)	12 in (305 mm)	1	1	6.7 lbs (3.04 kg)
CD805M	730573343586	14 in (356 mm) Height	8 in (203 mm)	14 in (356 mm)	1	1	6.8 lbs (3.08 kg)

TEST STANDARDS: ASTM E814 (UL 1479), CAN/ULC-S115, ASTM D4833



Permanent Solution

Specified Technologies Inc.
We engineer peace of mind.

Firestop, Smoke, & Sound Solutions

Click here to learn more about

