



LATEX-BASED GUN GRADE FIRESTOP SEALANT

## LC Endothermic Firestop Sealant

SpecSeal® LC Endothermic Firestop Sealant is a latex-based gun grade firestop sealant for construction joints and noncombustible penetrations. After application, LC Sealant cures to form a flexible seal against the propagation of fire. Under fire exposure, LC Sealant absorbs heat and release water vapor resisting the progress of smoke and flame.

### Features & Benefits

- Installer Friendly, easily applied with standard caulking gun
- Can be troweled on for larger applications
- Tested for up to 4 Hours of fire resistance when tested to ASTM E1966/UL2079, ASTM E814/UL1479, and CAN/ULC-S115
- Listed in over 80 UL® Tested Firestop Systems



### ORDERING INFORMATION

Catalog Number	UPC Number	Size	(UOM) Qty.	Case Qty.	Weight (Each)
LC150	730573011300	10.1 Oz Tube - 18.2 cu in (300 ml)	1	12	0.96 lbs (0.44 kg)
LC120	730573011331	20 Oz Sausage - 36 cu in (592 ml)	1	12	1.70 lbs (0.77 kg)
LC120GL	730573011461	20 Oz Sausage (Grey) - 36 cu in (592 ml)	1	12	1.70 lbs (0.77 kg)
LC120W	730573011348	20 Oz Sausage (White) - 36 cu in (592 ml)	1	12	1.70 lbs (0.77 kg)
LC129	730573011317	29 Oz Tube - 52 cu in (858 ml)	1	12	2.56 lbs (1.16 kg)
LC155	730573011355	5 Gallon Pail - 1,155 cu in (19 liters)	1	1	55.81 lbs (25.31 kg)
LC155W	730573039052	5 Gallon Pail (White) - 1,155 cu in (19 liters)	1	1	55.81 lbs (25.31 kg)



TEST STANDARDS: ASTM E814 (UL 1479), ASTM E1966 (UL 2079), CAN/ULC-S115

Deep Red Color

Grey Color

White Color

Permanent Solution

