

Intumescent Wrap Strip

SpecSeal® SSW Wrap Strips are available in a variety of sizes and types to tackle any combustible penetration. SSW Wrap Strips are available in 12 ft (3.7 m) rolls as well as individually pre-sized strips to minimize waste and speed up installation. When installed in conjunction with restraining steel, SSW Wrap Strips are able to collapse non-metallic piping of up to 12 in (304.8 mm) diameter!

Features & Benefits

- RED/RED2 for Plastic piping up to 6 in (152.4 mm) trade size
- BLU/BLU2 for Plastic piping up to 12 in (304.8 mm) trade size
- Tested in a variety of construction types
- Partners with other SpecSeal® Firestop Products



ORDERING INFORMATION

Catalog Number	UPC Number	Size	(UOM) Qty.	Case Qty.	Weight (Each)
SSWBLU	730573037010	12' x 2" x 3/16" (3.7 m x 51 mm x 4.8 mm) roll	1	8	2.87 lbs (1.30 kg)
SSWBLU2	730573037119	12' x 2" x 1/8" (3.7 m x 51 mm x 3.2 mm) roll	1	8	1.71 lbs (0.77 kg)
SSWRC	730573037508	2" width 30 Gauge sheet metal restraining collar for ≤4" (102 mm) trade size pipe, 25' (7.6 m) roll	1	1	6.47 lbs (2.93 kg)
WSC-8	730573037539	4" width preformed restraining collar for 6" (152 mm) and 8" (204 mm) trade size pipe	1	1	1.51 lbs (0.68 kg)
WSC-12	730573037607	5" width preformed restraining collar for 8" (204 mm) trade size pipe and larger	1	1	3.15 lbs (1.43 kg)

PRECUT WRAP STRIPS

SSWBLU220	730573037201	Precut strip sized for 2" (51 mm) trade size pipe	1	100	0.08 lbs (0.04 kg)
SSWBLU230	730573037300	Precut strip sized for 3" (76 mm) trade size pipe	1	100	0.22 lbs (0.10 kg)
SSWBLU240	730573037409	Precut strip sized for 4" (102 mm) trade size pipe	1	100	0.37 lbs (0.17 kg)

TEST STANDARDS: ASTM E814 (UL 1479), CAN/ULC-S115



ORDERING INFORMATION

SSWRED	730573037027	12' x 1-1/2" x 1/4" (3.7 m x 38 mm x 6.4 mm) roll	1	10	2.92 lbs (1.33 kg)
SSWRED2	730573037126	12' x 1-1/2" x 1/8" (3.7 m x 38 mm x 3.2 mm) roll	1	8	1.33 lbs (0.60 kg)
SSWRC2	730573037522	1-1/2" width 30 gauge sheet metal restraining collar for ≤4" 102 mm) trade size pipe, 25' (7.6 m) roll	1	1	5.19 lbs (2.35 kg)
WSC-8RED	730573037546	3" width preformed restraining collar for 6" (152 mm) trade size pipe	1	1	1.42 lbs (0.64 kg)

TEST STANDARDS: ASTM E814 (UL 1479), CAN/ULC-S115

