



HEAD-OF-WALL • WALL-TO-WALL • BOTTOM-OF-WALL

Track Top Gasket



Track Top Gasket makes short work of construction joints in gypsum board construction. It eliminates the need for firestop sealants or sprays by firestopping as the wall is constructed. Track Top Gasket is easily cut to length with scissors or a sharp knife, installing quick with no waste. And now, with newly added foam strips, TTG better conforms to rough concrete surfaces.

Features & Benefits

- Works with any ceiling track
- Tested for both standard and shaft wall construction
- Allows for 100% compression and extension
- Available in Red for easy identification and inspection
- Tested in head-of-wall, wall-to-wall, and bottom-of-wall joints
- New foam strips conform to concrete surfaces

Ordering Information

GYPSUM WALLS

Catalog Number	UPC Number	Description	(UOM) Qty.	Case Qty.	Weight (Each)	Width
TTG350F	730573083550	TTG for 3-1/2" (89 mm) to 3-5/8" (92 mm) ceiling tracks, 161 ft. (49 meters)	1	1	16.58 lbs (7.52 kg)	6.25" (159 mm)
TTG350FS	730573951996	TTG for multi width ceiling track, 161 ft. (49 meters)	1	1	16.58 lbs (7.52 kg)	6.25" (159 mm)
TTG600F	730573086049	TTG for 6" (152 mm) ceiling track, 161 ft. (49 meters)	1	1	23.47 lbs (10.65 kg)	8.63" (219 mm)
TTG350F2	730573950937	TTG for 3-1/2" (89 mm) to 3-5/8" (92 mm) ceiling tracks w/ foam, 40.5 ft. (12.3 meters)	1	1	5.4 lbs (2.45 kg)	6.25" (159 mm)
TTG350F2S	730573951033	TTG for multi width ceiling track w/foam, 40.5 ft. (12.3 meters)	1	1	5.5 lbs (2.50 kg)	6.25" (159 mm)
TTG600F2	730573950999	TTG for 6" (152 mm) ceiling track w/foam, 40.5 ft. (12.3 meters)	1	1	7.5 lbs (3.40 kg)	8.63" (219 mm)

GYPSUM SHAFT WALLS

Catalog Number	UPC Number	Description	(UOM) Qty.	Case Qty.	Weight (Each)	Width
TTG250J	730573082508	TTG for 2-1/2" (63.5 mm) J-Runners, 150 ft. (45.7 meters)	1	1	16.57 lbs (7.52 kg)	6.25" (159 mm)
TTG400J	730573084007	TTG for 4" (102 mm) J-Runners, 150 ft. (45.7 meters)	1	1	18.62 lbs (8.45 kg)	7.50" (191 mm)
TTG600J	730573086025	TTG for 6" (152 mm) J-Runners, 150 ft. (45.7 meters)	1	1	23.64 lbs (10.72 kg)	9.7" (248 mm)
TTG250J2	730573951019	TTG for 2-1/2" (63.5 mm) J-Runners w/foam, 40.5 ft. (12.3 meters)	1	1	6.5 lbs (2.95 kg)	6.25" (159 mm)
TTG400J2	730573951057	TTG for 4" (102 mm) J-Runners w/foam, 40.5 ft. (12.3 meters)	1	1	7.3 lbs (3.31 kg)	7.50" (191 mm)
TTG600J2	730573950975	TTG for 6" (152 mm) J-Runners w/foam, 40.5 ft. (12.3 meters)	1	1	9.3 lbs (4.22 kg)	9.7" (248 mm)

TEST STANDARDS: ASTM E1966, UL 2079, CAN/ULC-S115

