



Track Top Gasket makes short work of construction joints in gypsum board construction. It eliminates the need for firestop sealants or sprays by firestopping as the wall is constructed. Track Top Gasket is easily cut to length with scissors or a sharp knife, installing quick with no waste. And now, with newly added foam strips, TTG better conforms to rough concrete surfaces.

Features & Benefits

- Works with any ceiling track
- Tested for both standard and shaft wall construction
- Allows for 100% compression and extension
- Available in Red for easy identification and inspection
- Tested in head-of-wall, wall-to-wall, and bottom-of-wall joints
- New foam strips conform to concrete surfaces







Ordering Information

GYPSUM WALLS										
Catalog Number	UPC Number	Description	(UOM) Qty.	Case Qty.	Weight (Each)	Width				
TTG350F	730573083550	TTG with folded legs for 3 1/2" (89 mm) or 3 5/8" (92mm) ceiling track - 2x 80.5' (24.5 meter) rolls	1	1	16.57 lbs (7.52 kg)	6.25" (159 mm)				
TTG600F	730573086049	TTG with folded legs for 6" (152 mm) ceiling track - 2x 80.5' (24.5 meter) rolls	1	1	23.47 lbs (10.65 kg)	8.63" (219 mm)				
TTG350F2	730573950937	TTG for 3.5" (89 mm) to 3-5/8" (92 mm) ceiling track with foam, 40.5 ft. (12.3 meter) roll - Red Poly	1	1	5.4 lbs (2.45 kg)	6.25" (159 mm)				
TTG350F2-BK	730573950944	TTG for 3.5" (89 mm) to 3-5/8" (92 mm) ceiling track with foam, 40.5 ft. (12.3 meter) roll - Black Poly	1	1	5.4 lbs (2.45 kg)	6.25" (159 mm)				
TTG350F2S	730573951033	TTG for 3.5" (89 mm) to 3-5/8" (92 mm) ceiling track with foam, 40.5 ft. (12.3 meter) roll, factory split - Red Poly	1	1	5.5 lbs (2.50 kg)	6.25" (159 mm)				
TTG350F2S-BK	730573951040	TTG for 3.5" (89 mm) to 3-5/8" (92 mm) ceiling track with foam, 40.5 ft. (12.3 meter) roll, factory split - Black Poly	1	1	5.5 lbs (2.50 kg)	6.25" (159 mm)				
TTG600F2	730573950999	TTG for 6" (152 mm) ceiling track with foam, 40.5 ft. (12.3 meter) roll - Red Poly	1	1	7.5 lbs (3.40 kg)	8.63" (219 mm)				
TTG600F2-BK	730573951002	TTG for 6" (152 mm) ceiling track with foam, 40.5 ft. (12.3 meter) roll - Black Poly	1	1	7.5 lbs (3.40 kg)	8.63" (219 mm)				

GYPSUM SHAFT WALLS										
Catalog Number	UPC Number	Description	(UOM) Qty.	Case Qty.	Weight (Each)	Width				
TTG250J	730573082508	TTG for 2.5" (63.5 mm) J-Runners - 150' (45.7 meter) roll	1	1	16.57 lbs (7.52 kg)	6.25" (159 mm)				
TTG400J	730573084007	TTG for 4" (102 mm) J-Runners - 150' (45.7 meter) roll	1	1	18.62 lbs (8.45 kg)	7.50" (191 mm)				
TTG600J	730573086025	TTG for 6" (152 mm) J-Runners - 150' (45.7 meter) roll	1	1	23.64 lbs (10.72 kg)	9.7" (248 mm)				
TTG250J2	730573951019	TTG for 2.5" (63.5 mm) J-Runners with foam, 40.5 ft. (12.3 meter) roll - Red Poly	1	1	6.5 lbs (2.95 kg)	6.25" (159 mm)				
TTG250J2-BK	730573951026	TTG for 2.5" (63.5 mm) J-Runners with foam, 40.5 ft. (12.3 meter) roll - Black Poly	1	1	6.5 lbs (2.95 kg)	6.25" (159 mm)				
TTG400J2	730573951057	TTG for 4" (102 mm) J-Runners with foam, 40.5 ft. (12.3 meter) roll - Red Poly	1	1	7.3 lbs (3.31 kg)	7.50" (191 mm)				
TTG400J2-BK	730573951064	TTG for 4" (102 mm) J-Runners with foam, 40.5 ft. (12.3 meter) roll - Black Poly	1	1	7.3 lbs (3.31 kg)	7.50" (191 mm)				
TTG600J2	730573950975	TTG for 6" (152 mm) J-Runners with foam, 40.5 ft. (12.3 meter) roll - Red Poly	1	1	9.3 lbs (4.22 kg)	9.7" (248 mm)				
TTG600J2-BK	730573950982	TTG for 6" (152 mm) J-Runners with foam, 40.5 ft. (12.3 meter) roll - Black Poly	1	1	9.3 lbs (4.22 kg)	9.7" (248 mm)				

TEST STANDARDS: ASTM E1966, UL 2079, CAN/ULC-S115















