

WF

LATEX-BASED FIRESTOP CAULK FOR WOOD FRAME

## WF300 Intumescent Firestop Caulk

WF300 Intumescent Firestop Caulk is a latex-based firestop caulk designed for wood frame construction. WF300 Caulk is tested for penetrations in fire-rated gypsum/wood stud walls and framed floor/ceilings. Under fire exposure, WF300 expands (i.e. intumesces) up to four times to fill voids created by melting penetrants or wood shrinkage.

### Features & Benefits

- Easy to install; cleans up with water
- Water resistant when dry
- For combustible and noncombustible penetrants
- Tested to ASTM E814, UL1479, CAN/ULC-S115 for fire-ratings up to 3 hours



### ORDERING INFORMATION

Catalog Number	UPC Number	Size	(UOM) Qty.	Case Qty.	Weight (Each)
WF310	730573097106	10.1 Oz. Tube - 18.2 cu. in. (300 ml)	1	12	0.95 lbs (0.43 kg)
WF320	730573097205	20 Oz. Sausage - 36 cu. in. (592 ml)	1	12	1.70 lbs (0.77 kg)
WF305	730573097052	5 Gallon Pail - 1,155 cu. in. (19.0 liters)	1	N/A	54.30 lbs (24.63 kg)

**TEST STANDARDS:** ASTM E814 (UL1479), ASTM E1966 (UL2079), CAN/ULC-S115

Deep Red  
Color

Permanent  
Solution

ACOUSTICAL  
ULC 61  
(Relates to specific  
construction)

UL  
CERTIFIED

FBC  
SYSTEM COMPATIBLE