



SOLUTIONS FOR LARGE MOVEMENT DEFLECTION JOINTS

SpeedFlex® Joint Profile System

SpeedFlex® Joint Profile combines with SpecSeal® spray-applied coatings to provide unsurpassed joint movement capabilities in gypsum board construction. SpeedFlex® Joint Profile replaces traditional forming materials allowing for reduced application times and increased productivity.

Features & Benefits

- Allows 100% compression or extension
- Easy repair of cracked or deficient joints; simply cover and spray!
- Cost effective alternative to traditional joint forming materials



ORDERING INFORMATION

| Catalog Number | UPC Number | Size | (UOM) Qty. | Case Qty. | Weight (Each) |
|----------------|--------------|-------------------------------------|------------|-------------|--------------------|
| SFJP40 | 730573081440 | 4" (101.6 mm) x 43.38" (1101.85 mm) | 1 | 150 per box | 0.21 lbs (0.10 kg) |
| SFJP80 | 730573081457 | 8" (203.2 mm) x 43.38" (1101.85 mm) | 1 | 75 per box | 0.42 lbs (0.19 kg) |

TEST STANDARDS: ASTM E1966 (UL 2079), CAN/ULC-S115



1-800-992-1180
stifirestop.com



Click here to learn more about



ZSTI3539 01020