SOLUTIONS FOR LARGE MOVEMENT DEFLECTION JOINTS

SpeedFlex® Joint Profile System

SpeedFlex® Joint Profile combines with SpecSeal® spray-applied coatings to provide unsurpassed joint movement capabilities in gypsum board construction. SpeedFlex® Joint Profile replaces traditional forming materials allowing for reduced application times and increased productivity.

Features & Benefits

- Allows 100% compression or extension
- Easy repair of cracked or deficient joints; simply cover and spray!
- Cost effective alternative to traditional joint forming materials





ORDERING INFORMATION

Catalog Number	UPC Number	Size	(UOM) Qty.	Case Qty.	Weight (Each)
SFJP40	730573081440	4" (101.6 mm) x 43.38" (1101.85 mm)	1	150 per box	0.21 lbs (0.10 kg)
SFJP80	730573081457	8" (203.2 mm) x 43.38" (1101.85 mm)	1	75 per box	0.42 lbs (0.19 kg)

UL CERTIFIED **TEST STANDARDS:** ASTM E1966 (UL 2079), CAN/ULC-S115

Brown Color

Permanent Solution

Specified Technologies Inc.
Firestop, Smoke, & Sound Solutions

Click or scan to learn more

ZSTI3539 26202