



PREMIUM GRADE WATER-BASED INTUMESCENT FIRESTOP SEALANT

Intumescent Firestop Sealant

SpecSeal® SSS Firestop Sealant is a premium grade water-based Intumescent firestop sealant. SpecSeal® SSS Sealant incorporates our proprietary two-stage intumescent technology making it the go to choice for any combustible or non-combustible penetrants. As little as a 1/2" applied depth of SSS Sealant is required to provide up to a 4 Hr Fire resistance rating when tested to ASTM E814/UL 1479.

Features & Benefits

- Patented Two-Stage Intumescent Technology
- Easily works into tight spaces between penetrants
- Compatible with CPVC Piping
- Can be sanded and painted to match its surroundings
- Used in over 500 through-penetration UL® Tested Systems!



ORDERING INFORMATION

Catalog Number	UPC Number	Size	(UOM) Qty.	Case Qty.	Weight (Each)
SSS100	730573011003	10.1 oz. Tube (300 ml) 18.2 cu.in.	1	12	1.07 lbs (0.49 kg)
SSS129	730573011294	29 oz. Tube (858 ml) 52 cu. in.	1	12	2.84 lbs (1.29 kg)
SSS120	730573011034	20 oz. Sausage (592 ml) 36 cu. in.	1	12	1.86 lbs (0.84 kg)
SSS102	730573011027	2 Gal. Pail (7.6 liters) 462 cu.in.	1	N/A	23.29 lbs (10.56 kg)
SSS105	730573011058	5 Gal. Pail (19.0 liters) 1,155 cu.in.	1	N/A	62.45 lbs (28.33 kg)

TEST STANDARDS: ASTM E814 (UL1479), CAN/ULC-S115



1-800-992-1180
stifirestop.com



Click here to learn more about



ZSTI3531 11121