



LIGHT-WEIGHT, COST EFFECTIVE SOLUTION

SSM Firestop Mortar

SpecSeal® SSM Firestop Mortar is a lightweight and economical solution for large openings in concrete floors and walls. SpecSeal® Mortar mixes with water to form a slurry that can be pumped, poured, or troweled into the opening. SpecSeal® Mortar is quick setting to allow forms to be removed faster.

Features & Benefits

- Can be poured, pumped, or troweled in place
- Combines with other SpecSeal® Firestop Products
- Durable, permanent seal



ORDERING INFORMATION

| Catalog Number | UPC Number | Description | Packaging | Weight (Each) | Nom. Yield (Mixed) |
|----------------|--------------|--------------------------------------|-----------|----------------------|--------------------------------|
| SSM106 | 730573041062 | SpecSeal® Series SSM Firestop Mortar | Poly Pail | 22.87 lbs (10.37 kg) | 1,225 in ³ (20.1 L) |
| SSM22B | 730573042007 | SpecSeal® Series SSM Firestop Mortar | Fiber Bag | 22.41 lbs (10.17 kg) | 1,225 in ³ (20.1 L) |

TEST STANDARDS: ASTM E814 (UL1479), CAN/ULC-S115



1-800-992-1180
stifirestop.com



[Click here to learn more about](#)



ZSTI3541 11121