HIGH PERFORMANCE SILICONE FIRESTOP SEALANT

SIL300SL Silicone Firestop Sealant

SpecSeal® SIL300SL Silicone Firestop Sealant is a high-performance silicone firestop sealant tested to resist the passage of smoke, flame, and water in construction joints and penetration firestop systems. SIL300SL Sealant cures to form a flexible seal and carries a Class 1 W Rating for water resistance (per ANSI/UL1479).

The sealant is a one-part neutral curing silicone that will adhere to most building substrates without the use of primers. The sealant is low modulus minimizing the strain on the substrate surface while the elastomeric quality allows excellent recovery from extension and compression cycling.

Features & Benefits

- One-part, neutral-curing silicone
- Primerless adhesion to common jobsite substrates
- Elastomeric recovery after extension and compression
- Low-modulus formulation accommodates joint movement
- UV and ozone resistant for long-term durability
- Non-halogenated; contains no asbestos, PCBs, or inorganic fiber
- Listed in over 175 UL Tested Systems





ORDERING INFORMATION

Catalog Number	UPC Number	Size	(UOM) Qty.	Case Qty.	Weight (Each)
SIL305SL	730573013267	Self-Leveling 4.5 Gal. Pail (17.0 liters) 1,037 cu. in.	1	1	51.89 lbs (23.54 kg)
SIL320SL	730573013229	Self-Leveling 20 oz. Sausage Tube (592 ml) 36 cu. in	1	20	1.86 lbs (0.84 kg)

TEST STANDARDS: ASTM E814 (UL 1479), ASTM E1966 (UL 2079), CAN/ULC-S115

Limestone Color

Permanent Solution

Specified Technologies Inc.
Firestop, Smoke, & Sound Solutions

Click or scan to learn more

ZSTI3532 26125