

SpecSeal<sup>®</sup>  
**SIL**

HIGH PERFORMANCE SILICONE FIRESTOP SEALANT

## SIL300 Silicone Firestop Sealant

SpecSeal<sup>®</sup> SIL300 Silicone Firestop Sealant is a silicone firestop sealant tested to resist the passage of flames, smoke, hot gases, and water in construction joints and penetration firestop systems. SIL300 Sealant cures to form a flexible seal and carries a Class 1 W Rating for water tightness (Per ANSI/UL1479).

### Features & Benefits

- Available in a Gun Grade or Self Leveling
- Ozone and UV Resistant
- Excellent recovery from joint extension and compression
- Listed in over 175 UL<sup>®</sup> Tested Systems
- Excellent chemical resistance



### ORDERING INFORMATION

| Catalog Number | UPC Number   | Size  | (UOM) Qty. | Case Qty. | Weight (Each)        |
|----------------|--------------|---|------------|-----------|----------------------|
| SIL300         | 730573013106 | 10.1 oz Tube (300 ml) 18.2 cu. in.                      | 1          | 24        | 1.03 lbs (0.47 kg)   |
| SIL305         | 730573013052 | 4.5 Gal. Pail (17.0 liters) 1,037 cu. in.               | 1          | 1         | 54.43 lbs (24.69 kg) |
| SIL320         | 730573013205 | 20 oz. Sausage Tube (592 ml) 36 cu. in.                 | 1          | 12        | 1.86 lbs (0.84 kg)   |
| SIL305SL       | 730573013267 | Self-leveling 4.5 Gal. Pail (17.0 liters) 1,037 cu. in. | 1          | 1         | 51.89 lbs (23.54 kg) |
| SIL320SL       | 730573013229 | Self-leveling 20 oz. Sausage Tube (592 ml) 36 cu. in.   | 1          | 12        | 1.86 lbs (0.84 kg)   |



TEST STANDARDS: ASTM E814 (UL 1479), ASTM E1966 (UL 2079), CAN/ULC-S115

SIL300 Color: Concrete (Limestone)  
SIL300SL Color: Gray

Permanent Solution

**Specified Technologies Inc.**  
Firestop, Smoke, & Sound Solutions

Click or scan to learn more



ZST13532 25343