HIGH PERFORMANCE SILICONE FIRESTOP SEALANT

SIL400 Silicone Firestop Sealant


SpecSeal® SIL400 Silicone Sealant is a high-performance silicone firestop sealant tested to resist the passage of smoke, flame, and water in construction joints and penetration firestop systems. SIL400 Sealant cures to form a flexible seal and carries a Class 1 W Rating for water resistance (per ANSI/UL1479).

The sealant is a one-part, neutral-curing silicone that will adhere to most building substrates without the use of primers. The sealant is low modulus minimizing strain on the substrate surface while the elastomeric quality allows excellent recovery from extension and compression cycling.

Features & Benefits

- One-part, neutral-curing silicone
- Primerless adhesion to common jobsite substrates
- Elastomeric recovery after extension and compression
- Low-modulus formulation accommodates joint movement
- UV and ozone resistant for long-term durability
- Non-halogenated; contains no asbestos, PCBs, or inorganic fiber







Testing

- Where applicable, evaluated for Class 1 W-Rated systems (UL 1479)
- ASTM C920 Type S, Grade NS, Class 35 classification
- ASTM E84 (UL 1479) for penetrations
- ASTM E1966 (UL 2079) for dynamic construction joints
- Evaluated to CAN/ULC-S115 standard

ORDERING INFORMATION

Catalog Number	UPC Number	Size	(UOM) Qty.	Case Qty.	Weight (Each)
SIL400	730573952597	10.1 Oz Tube - 18.2 cu in (300 ml)	1	30	1.06 lbs (0.48 kg)
SIL405	730573952573	4.5 Gallon Pail -1,037 cu in (17.0 liters)	1	1	56.00 lbs (25.40 kg)
SIL420	730573952580	20 Oz Sausage - 36 cu in (592 ml)	1	15	1.86 lbs (0.84 kg)

CERTIFIED

TEST STANDARDS: ASTM E814 (UL 1479), ASTM E1966 (UL 2079), CAN/ULC-S115

Limestone Color

Permanent Solution

Specified Technologies Inc.
Firestop, Smoke, & Sound Solutions

Click or scan to learn more

ZSTI3532 26203