

## Intumescent Firestop Collars

SpecSeal® SSC Firestop Collars are factory-manufactured firestop devices sized to plastic pipes of up to 6 in (152 mm) trade size. SSC Collars consist of a restraining collar with a factory applied intumescent ensuring the correct amount of material is applied every time. Under fire exposure, SSC Collars quickly expand and collapse combustible piping forming a dense char, resisting the passage of smoke and flame.

## **Features & Benefits**

- Sized for 1.5 in (38 mm), 2 in (51 mm), 3 in (76 mm), 4 in (102 mm), 6 in (152 mm) trade size combustible Pipes
- · Installs quickly and eliminates waste
- Tested to CAN/ULC-S115 at 50 PA (0.20 in. water)





0	DD	<b>ERIN</b>	CIN	IEO	DM	ATL	OM
U	ΚU		U II	<b>VOIN</b>	KIVI	A	UN

Catalog Number	UPC Number	Size	(UOM) Qty.	Case Qty.	Weight (Each)
SSC150	730573031506	Firestop collar for 1.5" (38 mm) trade size plastic pipe	1	6	0.33 lbs (0.15 kg)
SSC200	730573032008	Firestop collar for 2.0" (51 mm) trade size plastic pipe	1	6	0.38 lbs (0.17 kg)
SSC300	730573033005	Firestop collar for 3.0" (76 mm) trade size plastic pipe	1	6	0.74 lbs (0.33 kg)
SSC400	730573034002	Firestop collar for 4.0" (102 mm) trade size plastic pipe	1	6	1.07 lbs (0.49 kg)
SSC600	730573036006	Firestop collar for 6.0" (152 mm) trade size plastic pipe	1	2	5.04 lbs (2.29 kg)

TEST STANDARDS: ASTM E814 (UL1479), CAN/ULC-S115











