



Elastomeric Spray

SpecSeal® AS200 Elastomeric Spray is a latex-based elastomeric firestop spray for construction joints and perimeter fire barrier applications. AS200 cures to form a durable seal that resists the passage of flames, hot gases, and smoke while allowing for dynamic joint movement.

Features & Benefits

- Applied with airless spray equipment
- Highly flexible to accommodate for dynamic joint conditions
- Tested for up to 4 Hour fire resistance rating when tested to ASTM E1966/UL 2079
- Listed in over 100 UL® Tested curtain wall and joint systems



ORDERING INFORMATION

Catalog Number	UPC Number	Size	(UOM) Qty.	Case Qty.	Weight (Each)
AS205	730573071076	5 Gallon Pail - 1,155 cu. in. (19 liters)	1	1	53.60 lbs (24.31 kg)
AS205BR	730573071182	5 Gallon Pail - 1,155 cu. in. (19 liters)	1	1	53.60 lbs (24.31 kg)
AS205W	730573071229	5 Gallon Pail - 1,155 cu. in. (19 liters)	1	1	53.60 lbs (24.31 kg)

TEST STANDARDS: ASTM E1966 (UL2079), CAN/ULC-S115, ASTM E90



Firestop, Smoke, & Sound Solutions
1 (800) 992-1180 stifirestop.com



Click here to learn more about

