SpecSeal® TTG

HEAD-OF-WALL SOLUTION

Track Top Gasket Flute Plug

SpecSeal® Track Top Gasket Flute Plug is a preformed firestop plug designed for use in conjunction with the Track Top Gasket (TTG) to protect head-of-wall joints in fluted steel deck construction. When installed together, the system delivers one- or two-hour fire resistance ratings while effectively sealing against fire, smoke and sound transmission.

The Flute Plug features a single, intumescent-coated plug engineered to fit standard steel deck flutes and installs from one side of the wall. A durable flame-retardant poly bag improves handling and supports clean, consistent installation alongside TTG.

Used together, the Track Top Gasket (TTG) and Flute Plug form a fully engineered, no-spray head-of-wall firestop solution, providing a cleaner, faster alternative to traditional stuff-and-spray systems without compromising performance.

Features & Benefits

- Preformed plugs fit into three standard sized steel deck flutes
- When paired with the SpeedFlex® Track Top Gasket, it offers a fully engineered Head-of-Wall solution for fluted decks with one or two-hour fire resistance ratings
- Permits installation from a single side and aids in project sequencing
- Reduces material waste
- Improves productivity on job sites





ORDERING INFORMATION

Catalog Number	UPC Number	Size	(UOM) Qty.	Case Qty.	Weight (Each)
TTG-FP1	730573952542	1-1/2" (38.1 mm) Flute Plug	1	180	0.17 lbs (0.08 kg)
TTG-FP2	730573952535	2" (50.8 mm) Flute Plug	1	80	0.34 lbs (0.15 kg)
TTG-FP3	730573952528	3" (76.2 mm) Flute Plug	1	60	0.48 lbs (0.22 kg)

TEST STANDARDS: ASTM E1966, UL2079, CAN/ULC-S115

Red Color

Permanent Solution

Specified Technologies Inc.
Firestop, Smoke, & Sound Solutions

Click or scan to learn more