






REQUEST FOR QUOTE

Contact Information					
Project Name:		Company Name:			
Company Address:		City:	State:	Zip:	
Point of Contact:		Email address:			
Phone:		Distributor:			
Site Information (ASCE 7-16)					
Site Address:		City:	State:	Zip:	
Exposure Category:	Occupance Category:	Max Wind Speed:			
Soil Type:	Ground Snow Load:	Average Land Slope & Direction:			
System Information					
PV Module make and model:					
Total modules in the system:		Module columns per Array:			
Fixed Tilt Angle (dimension A):		Maximum Ground Clearance (dimension B):			

Please include a site layout and module data sheet before emailing to solar@plp.com

Exposure Design Categories		
Exposure B	Terrain with buildings, forest, or surface irregularities covering at least 20% of the ground level area extending one mile or more from the site. Is generally an urban site. It is not expected that you make an exhaustive survey for one mile all around the array location to determine the exact proportion of building areas to land.	
Exposure C	Flat and generally open terrain extending one-half mile or more from the site in any full quadrant. This exposure has become the commonly accepted standard when the terrain is in an area not known.	
Exposure D	Represents the area with the most severe weather conditions. These areas have basic wind speeds of 80 mph or greater with flat, unobstructed terrain adjacent to large bodies of open water. Exposure D extends inland from the shore one-quarter mile or ten times the structure height; whichever is greater.	

Soil Classification Types		
Type 1	Crystalline Bedrock	
Type 2	Sedimentary and Foliated Rock	
Type 3	Sandy Gravel and/or Gravel	
Type 4	Sand, Silty or Clayey Sand, Silly Gravel, and Clayey Gravel	
Type 5	Clay, Sandy Clay, Silty Clay, Clayey Silt, Silt and Sandy Silt	





GLOBAL HEADQUARTERS 660 BETA DRIVE CLEVELAND, OHIO 44143 +1 440 461 5200 SOLAR@PLP.COM PLP.COM