

COYOTE[®] STP

The **COYOTE STP (Service Termination Point)** is a small scale, cost effective closure which provides an alternative to traditional network interface devices, while offering much greater application flexibility. The robust latch system, paired with an integrated over-molded cover, allows for quick re-entry and creates a secure seal over a wide range of cable profiles. The COYOTE STP is ideal for use where the optical network terminal (ONT) is on the inside of a premises.

FEATURES AND BENEFITS

- Dimensions: 10.1" x 5.0" x 1.9" (257 x 126 x 49 mm)
- Max Splice Capacity: 12 Single Fusion, 4 Mechanical
- Max Adapter Quantity: 2 Simplex SC or 2 Duplex LC
- Grommet Quantity: 2 (Multi-Hole Grommets Available)
- Grommet Cable Diameter Range: 0.100" – 0.425" (2.5 – 10.8 mm) Flat Drop and ROC™ Drop Cable
- Applications: Indoor/Outdoor Premises, Pedestal, Wall/Pole Network Interface Device (NID)
- Designed and tested in accordance with Telcordia[®] GR-771-CORE Above Grade, IP-67 Rated Requirements
- Constructed out of rugged UV-stabilized, flame-retardant material (UL94-5VA Rated)
- Robust latch system and integrated over-molded cover creates a secure seal and provides quick re-entry into the closure
- Removable splice platform allows splicing and connections to be made outside of the closure

ORDERING INFORMATION











COYOTE STP Catalog Number

STP- XX - X - X - X - X
 (Section 1) (Section 2) (Section 3) (Section 4) (Section 5)






Must be in
 alphabetical
 order

Catalog Number Example: STP-GG-3-1-2-2





Section 1

Grommet Selection (Select 2)	Cable Diameter Range
A 	SOLID / PLUG
B 	0.100" - 0.154" (2.5 - 3.9 mm) ROUND CABLES
C 	0.154" - 0.250" (3.9 - 6.4 mm) ROUND CABLES
D 	0.250" - 0.350" (6.4 - 8.9 mm) ROUND CABLES
E 	0.350" - 0.389" (8.9 - 9.9 mm) ROUND CABLES
F 	0.389" - 0.425" (9.9 - 10.8 mm) ROUND CABLES
G 	FOR FLAT DROP CABLES
H 	0.100" - 0.123" (2.5 - 3.1 mm) ROUND CABLES
J 	0.154" - 0.188" (3.9 - 4.8 mm) ROUND CABLES
R 	FOR ROC™ DROP CABLES (For Dielectric Drop Cables ONLY)

Section 2

Organizer Options (Select 1)	
1	 Splice Only
2	 Splice with Bonding & Grounding
3	 Cross-Connect
4	 Cross-Connect with Bonding & Grounding
5	 Direct Cross-Connect



Section 3

Adapter Type (Select 1)	
N	NONE
1	 SC/APC
2	 SC/UPC
3	 LC/APC
4	 LC/UPC

Section 4

Adapter Quantity
0 to 2

Section 5

Pigtails Required (Select 1) (Matches adapter type and quantity)	
N	NONE
1	 900 µm
2	 2 mm Jacketed

Accessories

Catalog Number	Description
80061322	COYOTE STP External Shroud Kit
80061323	COYOTE STP Pedestal Mounting Bracket Kit for Charles Industries PEDLOCK® BD4 and BD5 Buried Cable Pedestals

PEDLOCK® is a registered trademark of Charles Industries Ltd.
 ROC™ is a trademark of Corning Incorporated.