



## PROTECTOR TUBING

**Protector Tubing** has an overlapping design with 360 degree coverage and is slit for ease of application. Protector Tubing serves different functions. It protects the cable jacket from abrasion caused by structures, trees, and other cables, as well as protects energized lines from incidental contact with wildlife and vegetation.

### FEATURES AND BENEFITS

- Tubing slit configuration permits easy installation on existing conductor
- Durable EPDM tubing with a minimum thickness of 125 mils
- 500 V/mil dielectric strength
- Excellent resistance to ozone and petroleum-based solvents
- Overlapping profile follows bends and turns without risk of splitting open
- Profile accommodates distribution ranges of conductor applications
- Ideal for transformer stinger wires and arrestor connections
- Available in continuous rolls. Contact PLP with your requirements.



## ORDERING INFORMATION

### Protector Tubing

Catalog Number	Conductor Diameter Range		Length <sup>1</sup>	Weight per Unit	Quantity per Carton
	Minimum	Maximum			
	in (mm)	in (mm)	ft (m)	lb	
PT-0375	0.162 (4.1)	0.375 (9.5)	8 (2.43)	0.85	30
PT-0375-50			50 (15.24)	5.5	3
PT-0625	0.376 (9.6)	0.625 (15.8)	8 (2.43)	1.5	25
PT-0625-50			50 (15.24)	10	3
PT-0938	0.626 (15.9)	0.938 (23.8)	8 (2.43)	2.3	25
PT-0938-50			50 (15.24)	14	2
PT-1300	0.939 (23.9)	1.30 (33.0)	8 (2.43)	2.7	10
PT-1300-50			50 (15.24)	17	2

<sup>1</sup>Contact PLP for additional length options

**WARNING:** Protector tubing should not be used to protect humans from electrical shock.