



## PROTECTOR TUBING

**Protector Tubing** protects energized lines from faults due to incidental contact with various species of wildlife. The overlapping design provides 360° coverage of the conductor, even in jumper applications.

### FEATURES AND BENEFITS

- Tubing slit configuration permits easy installation on existing conductor
- Durable EPDM tubing with a minimum thickness of 125 mils
- 500 V/mil dielectric strength
- Excellent resistance to ozone and petroleum-based solvents
- Overlapping profile follows bends and turns without risk of splitting open
- New profile accommodates a wider range of conductor applications
- Ideal for transformer stinger wires and arrestor connections
- Available in continuous rolls. Contact PLP with your requirements.



## ORDERING INFORMATION

### Protector Tubing

Catalog Number	Conductor Diameter Range		Length <sup>1</sup>	Weight per Unit	Quantity per Carton
	Minimum	Maximum			
	in (mm)	in (mm)	ft (m)	lb	
PT-0375	0.162 (4.1)	0.375 (9.5)	8 (2.43)	0.85	30
PT-0375-50			50 (15.24)	5.5	3
PT-0625	0.376 (9.6)	0.625 (15.8)	8 (2.43)	1.5	25
PT-0625-50			50 (15.24)	10	3
PT-0938	0.626 (15.9)	0.938 (23.8)	8 (2.43)	2.3	25
PT-0938-50			50 (15.24)	14	2
PT-1300	0.939 (23.9)	1.30 (33.0)	8 (2.43)	2.7	10
PT-1300-50			50 (15.24)	17	2
PT-1750	1.31 (33.2)	1.75 (44.4)	8 (2.43)	5.7	10
PT-1750-50			50 (15.24)	36	3

<sup>1</sup>Contact PLP for additional length options

**WARNING:** Protector tubing should not be used to protect humans from electrical shock.