

VARI-GRIP™ LINK PLATES

VARI-GRIP Link Plates are designed to be an easy-to-install, anchoring accessory to VARI-GRIP Dead-Ends as an alternative to anchor shackles. The assemblies use bolt, nut, and cotter pin setup, offering security of anchor shackles. VARI-GRIP Link Plates can be used in new construction and retrofit applications. PLP's VARI-GRIP Link Plates are designed to hold 100% of the rated breaking strength (RBS) installed.




FEATURES AND BENEFITS

- Made of hot-dipped galvanized steel
- Bolt, nut, and cotter pin for durability and security
- Rated for 100% of the RBS of the strand installed
- Works with dual or single anchor plates
- Comes pre-assembled for ease of installation
- Can be used with galvanized steel EHS strand and Bridge strand






VARI-GRIP™ LINK PLATES

For use with Gen 1 VARI-GRIP Dead-Ends

Catalog Number	Max Strength Rating	VARI-GRIP Dead-End Size	Conformal Casting	U-bolt Size	Through Hole Diameter	Structural Bolt Diameter	Image
	lb						
VLP-0600	42,400	VG-X-2100 VG-X-2101 VG-X-2108	N/A	5-8" - 3/4"	1"	7/8"	
VLP-0606	192,000	VG-X-2107 VG-X-4109 VG-X-5110 VG-X-5111	00060169	1-1/2"	2-3/8"	2"	
VLP-0607	252,000	VG-X-4110 VG-X-4111 VG-X-5112 VG-X-5113 VG-X-5114	00060169	1-3/4"	2-3/8"	2-1/4"	

NOTE: 'X' in VARI-GRIP Size can be 0 or 18 for 0" and 18" takeup, respectively.

For use with Gen 2 VARI-GRIP Dead-Ends

Catalog Number	Max Strength Rating	VARI-GRIP Dead-End Size	Conformal Casting	U-bolt Size	Through Hole Diameter	Structural Bolt Diameter	Image
	lb						
VLP-0601	79,000	VG-X-2103BR VG-X-2104BR VG-X-5105BR	N/A	1"	1-1/2"	1-1/4"	
VLP-0603	104,000	VG-X-2104BR VG-X-2105BR VG-X-5105BR	N/A	1-1/8"	1-1/2"	1-3/8"	
VLP-0604	156,000	VG-X-2105BR VG-X-2106BR VG-X-4108BR VG-X-5107BR VG-X-5108BR VG-X-5109BR	N/A	1-1/8"	1-7/8"	1-1/2"	

NOTE: 'X' in VARI-GRIP Size can be 0 or 18 for 0" and 18" takeup, respectively.

