

FRONTIER

TAS
FLOORING

GLUE DOWN | 5.0 MM, 20 MIL

Construction	Luxury Vinyl Plank
Classification	ASTM F1700, Class III, Type B
Dimensions	7.25" Wide x 48" Long (185 mm x 1226 mm)
Overall Thickness	5.0 mm
Wear Layer	20 mil
Finish Coat	Polyurethane
Texture	Random Embossed-In-Register & Smooth
Edge Profile	Micro Bevel
Packaging	21.97 sf/ctn, 9 pcs/ctn, 41.2 lbs/ctn, 55 ctn/plt, 1208.5 sf/plt

Installation & Maintenance

Glue Down

Ambient & Surface Temperature at Installation: 60 - 85 Degrees Fahrenheit

Maintenance: No Wax, Neutral PH cleaner, such as TAS Flooring Fresh Floors.

Recommended Adhesive: -Dynamic, Transitional Pressure Sensitive, firm set
-Pinnacle, Premium Transitional Pressure Sensitive, hard set


Test Method & Requirements

Solid Vinyl Floor Tile	ASTM F1700	Pass
Flexibility	ASTM F137	Pass
Thickness	ASTM F386	Pass
Wear Layer Thickness	ASTM F410	Pass
Resistance to Heat Color Change	ASTM F1514	Pass
Resistance to Light Color Change	ASTM F1515	Pass
Residual Indentation	ASTM F1914	Pass
Size & Squareness	ASTM F2199	Pass
Static Coefficient of Friction Polished Surface	ASTM D2047	Exceeds Standard
Static Load Limit	ASTM F970	Pass > 250 LBS
Flammability/Radiant Flux	ASTM E648	Class I
Smoke Density	ASTM E662	Pass

Health & Environmental

FloorScore SCS Certified

Phthalate-Free



Warranty


10 Year Light Commercial, 30 Year Multifamily Residence,
Lifetime Residential

Accessories


[QNose](#) Stair Nosing

Layout Options:


NOT TO SCALE




HERRINGBONE




TRIPLE HERRINGBONE



FIVE PLANK PARQUET



ASHLAR



STAGGER

