

Super Nop Tiles

General Information



This product must be installed by professional installers that have sufficient professional liability insurance coverage (aka ‘Errors and Omission’ insurance) for the project. Matter Surfaces recommends installing and maintaining entrance matting at all outdoor entrances and transitions from warehouse to office space; this will improve air quality and lengthen the life of floors.

Proper glides must be used on all furniture that may slide directly across the matting. Heavy objects must not be moved directly across the matting; use protective boards.

Direct sunlight can cause UV damage, such as fading, to most interior finishes. Low E glass should be selected to reduce the UV transmission to less than 1%. If Low E glass is not an option, applying 3M™ Sun Control Window Film, or similar, on the windows is recommended. Areas of the flooring subjected to direct sunlight must be shielded for two hours before, during and for a period of (72) hours after the installation.

Product	Entryway Matting Tile
Construction	Needlepunch
Fiber	Solution Dyed UV Stabilized Polypropylene Fiber
Backing	Bitumen
Use Class	Commercial 33
CleanZone™	Zone 3 Lobby
Recommended Adhesive	MI 1000
Dimensions	19.7” x 19.7” (50 x 50 cm)
Total Height	12.5 mm (1/2”)
Face Weight	52 oz / yd²
Total Weight	141 oz / yd²

	Performance	Result
Surface Flammability	ASTM 2859	Passes
Coefficient of Friction	ASTM D2047	0.51
Color Fastness to Light	AATCC 16-04	Pass / No Change