



Night Rush | SCLA0301



Brimstone | SCLA0302



Harbinger Run | SCLA0303



Canyon Thunder | SCLA0304



Alder Ridge | SCLA0305

SPECIFICATIONS

Construction	Waterproof Laminate
Dimensions	7 3/4" Wide x 48" Long (195 mm x 1215 mm)
Overall Thickness	10 mm (Includes 2 mm Pad)
Wear Surface	AC3 Rated
Texture	Low Gloss, Embossed
Edge Profile	4-Sided Painted Bevel
Packaging	20.4 sf/ctn, 8 pcs/ctn, 30.6 lbs/ctn, 55 ctn/plt, 1122 sf/plt
Installation	Angle/Angle
Warranty	5 Year Light Commercial, 5 Year Multifamily Common Areas 25 Year Residential

INSTALLATION FAST FACTS

- Radiant Heat: Approved (Hydro Systems ONLY)
- Acclimate product to normal room conditions
- Leave 3/8" expansion for areas over 25'
- Transitions required for rooms larger than 45'L or 45"W
- Subfloors dry and flat (3/16" in 10')
- Installation on or below grade concrete requires 6 mil moisture barrier

Read Complete Instructions Before Installing



tasflooring.com

**SPEC SHEET
WARRANTY
INSTALLATION & MAINTENANCE
TRIMS, TRANSITIONS & QNOSE**

