

WATERPROOF AC4 LAMINATE | 10 MM + 2.0 MM PAD



Aristides | DWLA0201



Barton | DWLA0202



Whitney | DWLA0203



Canfield | DWLA0204



Ascot | DWLA0205



Oakley | DWLA0206



Aintree | DWLA0207



Belmont | DWLA0208



Haskell | DWLA0209



Woodward | DWLA0210

SPECIFICATIONS

Construction	Waterproof Laminate
Classification	EN13329
Dimensions	9.25" Wide x 72" Long (238 mm x 1830 mm)
Overall Thickness	12 mm (Includes 2 mm Pad)
Wear Surface	AC4 Rating
Texture	Embossed-In-Register
Edge Profile	4-Sided Painted Bevel
Packaging	23.47 sf/ctn, 5 pcs/ctn, 45.1 lbs/ctn, 52 ctn/plt, 1220.4 sf/plt
Installation	Angle/Angle
Warranty	Waterproof, Lifetime Residential, 15 Year Light Commercial

INSTALLATION FAST FACTS

- Radiant Heat: Approved (Hydro Systems ONLY)
- Acclimate product to normal room conditions
- Leave 3/8" expansion for areas over 25'
- Transitions required for rooms larger than 45'L or 45"W
- Subfloors dry and flat (3/16" in 10')
- Installation on or below grade concrete requires 6 mil moisture barrier

Read Complete Instructions Before Installing



tascontract.com

**SPEC SHEET
WARRANTY
INSTALLATION & MAINTENANCE**

