

# TANDEM ESSENCE



WPC | 7.5 MM, 20 MIL



**Atlantis** | DGWP0401



**Baylis** | DGWP0402



**Allison** | DGWP0403



**Winthrop** | DGWP0404



**Belvedere** | DGWP0405



**Hawke** | DGWP0406

## SPECIFICATIONS

Construction	WPC Vinyl Click, Wood Plastic Composite
Classification	ASTM F3261
Dimensions	7" Wide x 60" Long (178 mm x 1500 mm)
Overall Thickness	7.5 mm (Includes 2 mm Pad)
Wear Layer	20 mil
Finish Coat	Adamantine Finish™ Scratch, Stain, Wear Resist
Texture	Random Embossed-In-Register
Edge Profile	Micro-Bevel
Packaging	22.99 sf/ctn, 8 pcs/ctn, 29.45 lbs/ctn, 75 ctn/plt, 1724.25 sf/plt
Installation	Angle/Angle, Float
Warranty	10 Year Light Commercial, 10 Year Multifamily, 30 Year Residential

## INSTALLATION FAST FACTS

- Transitions required in rooms over 50' x 50' or 875 sf
- Acclimate to Normal Room Conditions (NRC) 65°F - 85°F
- Expansion Space: 1/4" gap
- Ambient RH Between 35% to 60%
- Work out of several boxes, mixing product for visual appearance
- Hydro Radiant Heat approved (≤ 85°F)

Read Complete Instructions Before Installing



SPEC SHEET, WARRANTY  
INSTALLATION & MAINTENANCE

tasflooring.com

