

TANDEM PREMIUM



WPC | 8.0 MM, 20 MIL



Brook Hill | VRWP0101



Kenton | VRWP0102



Woodford | VRWP0103



Featherstone | VRWP0104



Hatfield | VRWP0105



Dunbar | VRWP0106



Holloway | VRWP0107



Sunderland | VRWP0108

SPECIFICATIONS

Construction	Engineered WPC Vinyl Click
Classification	ASTM F3261, Class I, Type B, Grade 1, Class B
Dimensions	9" Wide x 60" Long (224 mm x 1518 mm)
Overall Thickness	8.0 mm (Includes 1.5 mm Pad)
Wear Layer	20 mil
Finish Coat	Adamantine Finish™ Scratch, Stain, Wear Resist
Texture	Embossed-In-Register
Edge Profile	Pressed Bevel
Packaging	29.307 sf/ctn, 8 pcs/ctn, 50.7 lbs/ctn, 52 ctn/plt, 1524 sf/plt
Installation	Angle/Angle, Float
Warranty	10 Year Light Commercial, 30 Year Residential

INSTALLATION FAST FACTS

- Acclimate to Normal Room Conditions (NRC) 65°F - 85°F
- Expansion Space: 1/4" gap
- Ambient RH Between 35% to 60%
- Work out of several boxes, mixing product for visual appearance

Read Complete Instructions Before Installing



SPEC SHEET
WARRANTY
INSTALLATION & MAINTENANCE

tasflooring.com

