

# NOBILITY

**TAS**  
FLOORING

GLUE DOWN | 2.5 MM, 12 MIL



**Atticus** | NOLV0701



**Bentley** | NOLV0702



**Dalton** | NOLV0703



**Giles** | NOLV0704



**Kingsley** | NOLV0705



**Roland** | NOLV0706

## SPECIFICATIONS

|                   |                                                                  |
|-------------------|------------------------------------------------------------------|
| Construction      | Solid Vinyl Tile                                                 |
| Classification    | ASTMF 1700                                                       |
| Dimensions        | 7" Wide x 48" Long (177.8 mm x 1219.2 mm)                        |
| Overall Thickness | 2.5 mm                                                           |
| Wear Layer        | 12 mil                                                           |
| Finish Coat       | Polyurethane                                                     |
| Texture           | Embossed                                                         |
| Edge Profile      | Square                                                           |
| Packaging         | 35 sf/ctn, 15 pcs/ctn, 30.5 lbs/ctn, 60 ctn/plt, 2100 sf/plt     |
| Installation      | Glue Down                                                        |
| Warranty          | 5 Year Light Commercial, 5 Year Multifamily, 25 Year Residential |

## INSTALLATION FAST FACTS

- Acclimate to Normal Room Conditions (NRC) 65°F - 85°F
- Expansion Space: 1/4" gap
- Ambient RH Between 35% to 60%
- Work out of several boxes, mixing product for visual appearance

Read Complete Instructions Before Installing



tascontract.com

SPEC SHEET  
WARRANTY  
INSTALLATION & MAINTENANCE



**TAS**  
CONTRACT