AGATEWOOD

TAS FLOORING

SPC | 6.0 MM, 20 MIL

Eagledale | SCRC0101

Windsong | SCRC0102

Blakley | SCRC0103

Windslow | SCRC0104

Hawley | SCRC0105

Fletcher | SCRC0106

Tracyton | SCRC0107

Ferncliff | SCRC0108

SPECIFICATIONS

Construction	SPC, Stone Polymer Composite, Rigid Core
Classification	ASTM F3261, Class I, Type B, Grade 1, Class B
Dimensions	9" Wide x 60" Long, 228 mm x 1524 mm
Overall Thickness	6.0 mm (Includes 1.5 mm pad)
Wear Layer	20 mil
Finish Coat	Low Gloss, Polyurethane
Texture	Embossed
Edge Profile	4-Sided Painted Bevel
Packaging	22.44 sf/carton - 56 cartons/pallet - 1256.6 sf/pallet
Installation	Angle / Angle, Float
Warranty	10 Yr Light Commercial, 10 Yr Multi-Family, 30 Yr Residential

INSTALLATION FAST FACTS

- Transitions required for rooms larger than 50' W x 50' L
- Acclimate to Normal Room Conditions (NRC) 60°F - 85°F
- Hydro Radiant Heat approved (≤ 85°F)
- Expansion Space: 1/4" gap
- Ambient RH Between 35% to 55%
- Floor Flatness to 1/8" in 6'
- Floating floors must be allowed to expand and contract with no restrictions

Read Complete Instructions Before Installing

tascontract.com

SPEC SHEET
WARRANTY
INSTALLATION & MAINTENANCE
TRIMS, TRANSITIONS & QNOSE

floor score
SCScertified

Waterproof

Wide Plank

Painted Bevel

TAS CONTRACT