

WATERPROOF AC3 | 8 MM + 2.0 MM PAD

Construction	Waterproof Laminate
Classification	EN 13329
Dimensions	7.75" Wide x 48" Long (196 mm x 1215 mm)
Overall Thickness	10 mm (Includes 2 mm IXPE Pad)
Attached Pad	2 mm Premium IXPE Pad
Surface Finish	AC3
Texture	Standard
Edge Profile	4-Sided Painted Bevel
Packaging	30.785 sf/plt, 12 pcs/ctn, 47.84 lbs/ctn, 30 ctn/plt, 923.6 sf/plt

Installation & Maintenance

Angle/Angle

Ambient & Surface Temperature at Installation: Acclimate product to environment

Maintenance: No Wax, Neutral PH cleaner, such as TAS Flooring Fresh Floors

Expansion & Transition: 3/8" expansion; max room size w/o transition 40x40

Test Method & Requirements


Standard Laminate	EN 13329	Pass
Thickness (with Pad)	ASTM F386/ (387)	Pass
Wear Layer Thickness	ASTM F410	Pass
Squareness of Element	ANNEX A	Pass
Height Difference of Element	ANNEX B	Pass
Opening Between Element	ANNEX B	Pass
Tabor Abrasion	ANNEX E	Pass
Large Ball	ANNEX F	Pass
Small Ball	ANNEX F	Pass
24 Hour Thickness Swelling	ANNEX G	Pass
Resistance to Staining	EN 438	Pass
HPLC Gradient Chemical Analysis		Pass
Pull Test		Pass

Impact Insulation Class IIC	ASTM E492*
Sound Transmission Class STC	ASTM E90*

*The flooring assembly dictates IIC, STC, HIIC, and Low IIC results; contact your representative for specific testing.

Health & Environmental

Carb Phase II Compliant
GreenGuard Gold



Warranty


Waterproof, 25 Year Residential

Accessories


Trims: T Mold, Reducer, End Cap, Stair Nose, Quarter Round,
[QNose](#) Stair Nose

Layout Options:

NOT TO SCALE



ASHLAR



STAGGER

