

ACOUSTIC GLUE DOWN



Alma



Above



Align



Balance



Balboa



Below



Capetown



Compass



Dixon



Even



Gardenia



Grade



Grafton



Gibraltar



Havanna



Horizon

ACOUSTIC GLUE DOWN



Lisbon



Mimosa



Monaco



Monitor



Oria



Parnell



Primrose



Sloop



Sorrento



True



Turlock



Tupelo



Plane



Uniform



Wayne



Winona

ACOUSTIC GLUE DOWN

Construction	Acoustic Glue Down Luxury Vinyl
Classification	ASTM F1700, Class III, Type B
Dimensions (nominal)	7" x 48"
Overall Thickness	3.5 mm (attached Pad) or 5.0 mm (attached Pad)
Wear Layer Thickness	12 mil or 20 mil
Finish Coat	UV Cured Polyurethane or Ceramic Bead Enhanced
Texture	Embossed
Edge Profile	Squared or Eased Edge

Warranty

5 Yr Light Commercial, 25 Yr Multi-Family Residence Units, 5 Yr Multi-Family Common Area, 25 Yr Residential Warranty

Installation

Glue Down Adhesive: Light Commercial, Multi-family - WF Taylor Dynamic

Glue Down Adhesive: Commercial - WF Taylor Pinnacle

Test Methods & Requirements

Solid Vinyl Tile	ASTM F1700	Pass
Flexibility	ASTM F137	Pass
Thickness	ASTM F386	Pass
Wear Layer Thickness	ASTM F410	Pass
Resistance to Heat	ASTM F1514	Pass
Resistance to Light	ASTM F1515	Pass
Residual Indentation	ASTM F1914	Pass
Size & Squareness	ASTM F2421, F2055	Pass
Static Coefficient Polished Surface	ASTM D2047	Pass
Static Load Limit	ASTM F970	Pass
Flammability/Radiant Flux	ASTM E648	Pass
Smoke Density	ASTM E662	Pass
Resistance to Chemicals	ASTM F925	Pass
Dimensional Stability	ASTM F2199	Pass
Impact Noise (IIC)	ASTM E492	IIC 63 w/suspended ceiling

