

GLUE DOWN | 2.0 MM, 12 MIL



Winona | NOLV0501



Wayne | NOLV0502



Tupelo | NOLV0503



Grafton | NOLV0504



Alma | NOLV0505



Dixon | NOLV0506



Turlock | NOLV0507



Parnell | NOLV0508

SPECIFICATIONS

Construction	Luxury Vinyl Tile
Classification	ASTM F1700
Dimensions (nominal)	7" Wide x 48" Long, 177.8 mm x 1219.2 mm
Overall Thickness	2.0 mm
Wear Layers	12 mil
Finish Coat	Polyurethane
Texture	Embossed
Edge Profile	Square Edge
Packaging	51.33 sf/ctn, 22 pcs/ctn, 36 lbs/ctn, 50 ctn/plt, 2566.5 sf/plt
Warranty	5 Yr Light Commercial, 25 Yr Residential

INSTALLATION FAST FACTS

- Acclimate to Normal Room Conditions (NRC) 65°F - 85°F
- Expansion Space: 1/4" gap
- Ambient RH Between 35% to 60%
- Work out of several boxes, mixing product for visual appearance

Read Complete Instructions Before Installing



tasflooring.com

SPEC SHEET
WARRANTY
INSTALLATION & MAINTENANCE

