

AC4 | 10 MM + 2.0 MM PAD

Construction	Laminate
Classification	EN 13329
Dimensions	7.75" Wide x 48" Long (196 mm x 1216 mm)
Overall Thickness	12 mm (Includes 2 mm Pad)
Attached Pad	2 mm Premium IXPE Pad
Surface Finish	AC4 - Moderate Commercial Use
Texture	Embossed In Register
Edge Profile	4-Sided Painted Bevel
Packaging	15.39 sf/ctn, 6 pcs/ctn, 28.4 lbs/ctn, 65 ctn/plt, 1004 sf/plt

Installation & Maintenance

Angle/Angle

Ambient & Surface Temperature at Installation: Acclimate product to environment

Maintenance: No Wax, Neutral PH cleaner, such as T&A Supply Fresh Floors

Expansion & Transition: 3/8" expansion; max room size w/o transition 40x40

Test Method & Requirements


Standard Laminate	EN 13329	Pass
Thickness (with Pad)	ASTM F386/ (387)	Pass
Wear Layer Thickness	ASTM F410	Pass
Squareness of Element	ANNEX A	Pass
Height Difference of Element	ANNEX B	Pass
Opening Between Element	ANNEX B	Pass
Tabor Abrasion	ANNEX E	Pass
Large Ball	ANNEX F	Pass
Small Ball	ANNEX F	Pass
24 Hour Thickness Swelling	ANNEX G	Pass
Resistance to Staining	EN 438	Pass
HPLC Gradient Chemical Analysis		Pass
Pull Test		Pass
Impact Insulation Class IIC	ASTM E492*	
Sound Transmission Class STC	ASTM E90*	

*The flooring assembly dictates IIC, STC, HIIC, and Low IIC results; contact your representative for specific testing.

Health & Environmental

FloorScore SCS Certified

Carb Phase II Compliant



Warranty


15 year Light Commercial, 80 Hour Topical, Lifetime Residential

Accessories


[QNose](#) Stair Nose

Layout Options:

NOT TO SCALE



ASHLAR



STAGGER

