FRONTIER

TAS FLOORING

GLUE DOWN | 5.0 MM, 20 MIL



Iona | DGLV0301



Sandoval | DGLV0302



Churchill | DGLV0303



Banderin | DGLV0304



Forsyth | DGLV0305



Logan | DGLV0306



Rockbridge | DGLV0307



Kodiak | DGLV0308

SPECIFICATIONS

Construction	Flexible Luxury Vinyl Plank
Classification	ASTM F1700, Class III, Type B
Dimensions	7" Wide x 48" Long (177.8 mm x 1219 mm)
Overall Thickness	5.0 mm
Wear Layer	20 mil
Finish Coat	Polyurethane
Texture	Embossed
Edge Profile	Micro Bevel
Packaging	23.33 sf/ctn, 10 pcs/ctn, 44.85 lbs/ctn, 50 ctn/plt, 1166.5 sf/plt
Installation	Glue Down
Warranty	10 Year Light Commercial, 30 Year Multifamily Residence, Lifetime Residential

INSTALLATION FAST FACTS

- Acclimate to Normal Room Conditions (NRC) 65°F - 85°F
- Expansion Space: 1/4" gap
- Ambient RH Between 35% to 60%
- Work out of several boxes, mixing product for visual appearance
- Minimum 3500 PSI for Concrete/Gypcrete Substrates

Read Complete Instructions Before Installing

tascontract.com

SPEC SHEET
WARRANTY
INSTALLATION & MAINTENANCE

floor score
SCScertified

PHTHALATE FREE

Hydronic Heat

Double fiberglass

Glue

TAS CONTRACT

Additional specifications, full installation, maintenance and warranty information available online at **TASCONTRACT.COM**.

A division of T&A supply company, Inc.