

SIERRA TILE



SPC | 6 MM, 12 MIL



Cotto Beige | DGRC1401



Limestone White | DGRC1402



Hermes Gray | DGRC1403



Pulpis Brown | DGRC1404



Sand White | DGRC1405



Italian Grey Sand | DGRC1406

SPECIFICATIONS

Construction	Rigid Polymeric Core Waterproof
Classification	ASTM F3261, Class I, Type B, Grade 1, Class B
Dimensions	12" Wide x 24" Long (300 mm x 600 mm)
Overall Thickness	6.0 mm (Includes 1.0 mm Pad)
Attached Pad	1.0 mm
Wear Layer	12 mil
Finish Coat	Polyurethane
Texture	Embossed
Edge Profile	Painted Bevel

INSTALLATION FAST FACTS

- No Transitions in under 2,500 sf
- Acclimate to Normal Room Conditions (NRC) 65°F - 85°F
- Hydro Radiant Heat approved ($\leq 85^{\circ}\text{F}$)
- Expansion Space: 1/4" gap
- Ambient RH Between 35% to 60%
- Work out of several boxes, mixing product for visual appearance
- Hydro Radiant Heat approved ($\leq 85^{\circ}\text{F}$)

Read Complete Instructions Before Installing



tascontract.com

**SPEC SHEET, WARRANTY
INSTALLATION & MAINTENANCE
TRIMS, TRANSITIONS & [QNOSE](#)**



Additional specifications, full installation instructions & warranty information available online at tascontract.com



TAS supply company, Inc.