

EQUINOX MULTI



WATERPROOF LAMINATE | 12 MM + 1.5 MM PAD

Construction	Waterproof Laminate
Classification	EN 13329
Dimensions	7.5" Wide x 48" Long
Overall Thickness	13.5 mm (includes 1.5 mm EVA Pad)
Attached Pad	1.5 mm EVA Pad
Wear Surface	AC4
Texture	EIR or Embossed
Edge Profile	4-Sided Micro-Bevel
Packaging	22.54 sf/ctn, 33 ctn/plt, 743.82 sf/plt

Installation & Maintenance

TightLock (Drop/Tap)

Transition: Transition required for rooms larger than 66' W x 66' L.

Ambient & Surface Temperature at Installation: 60 - 85 Degrees Fahrenheit

Maintenance: No Polish, Fresh Floors by Taylor


Test Method & Requirements

Standard Laminate	EN 13329	Pass
Thickness (with Pad)	ASTM F386/ (387)	Pass
Wear Layer Thickness	ASTM F410	Pass
Squareness of Element	ANNEX A	Pass
Height Difference of Element	ANNEX B	Pass
Opening Between Element	ANNEX B	Pass
Tabor Abrasion	ANNEX E	Pass
Large Ball	ANNEX F	Pass
Small Ball	ANNEX F	Pass
24 Hour Thickness Swelling	ANNEX G	Pass
Resistance to Staining	EN 438	Pass
HPLC Gradient Chemical Analysis		Pass
Pull Test		Pass
Impact Insulation Class IIC	ASTM E492*	
Sound Transmission Class STC	ASTM E90*	

*The flooring assembly dictates IIC, STC, HIIC, and Low IIC results; contact your representative for specific testing.

Health & Environment

GreenGuard Gold



Warranty

Waterproof, 12 Yr Light Commercial, 15 Year Multi-Family, Lifetime Residential

Accessories

Trims: T Mold, Reducer, End Cap, Stair Nose, Quarter Round

[QNose](#) Stair Nosing

Layout Options:

