

ABA LSPC 10 MM, 20 MIL



Maestro | WIRC0601



Bacchus | WIRC0602



Orion | WIRC0603



Pedestal | WIRC0604



Virtuoso | WIRC0605



Spectrum | WIRC0606



Provost | WIRC0607



Thaddeus | WIRC0608

SPECIFICATIONS

Construction	LSPC Hybrid Luxury Vinyl, ABA Foam Rigid Core
Classification	ASTM F3261, Class I, Type B, Grade 1, Class B
Dimensions	7.125" Wide x 60" Long, 181 mm x 1524 mm
Overall Thickness	10 mm (includes 2 mm IXPE pad)
Wear Layer	20 mil
Finish Coat	Adamantine Finish™ Scratch, Stain, Wear Resist
Texture	Embossed
Edge Profile	4-Sided Painted Bevel
Packaging	23.75 sf/carton - 30 carton/pallet - 712.5 sf/pallet
Installation	Angle / Angle
Warranty	30 Yr Residential, 10 Yr Light Commercial, 10 Yr Multi-Family

INSTALLATION FAST FACTS

- Transitions required for rooms larger than 50' W x 50' L
- Acclimate to Normal Room Conditions (NRC) 60°F - 85°F
- Hydro Radiant Heat approved (≤ 85°F)
- Expansion Space: 1/4" gap
- Ambient RH Between 35% to 55%
- Floor Flatness to 3/16" in 10'

Read Complete Instructions Before Installing



tasflooring.com

**SPEC SHEET
WARRANTY
INSTALLATION & MAINTENANCE
TRIMS, TRANSITIONS & QNOSE**

