

ARTESIAN WOODS

GLUE DOWN | 3.0 MM, 20 MIL | 7" X 60"















QNose Stair Nosing is made from the same material as your flooring selection, allowing for better coordination with your installed floors.







SUPERIOR STABILITY

Featuring an AB-core structure, the Artesian Woods Collection offers enhanced dimensional stability. The innovative five-roller co-extrusion process seamlessly molds the layers, reducing vertical deflection and improving overall stability, making it ideal for residential, multifamily and commercial applications.



ECO-FRIENDLY

Made from PVC and natural stone powder, this collection is free from radioactive elements and harmful gases. The plastic molding process ensures zero formaldehyde release, providing a phthalates-free and environmentally safe flooring solution.



100% WATERPROOF

The Artesian Woods Collection is completely waterproof, with no affinity for water due to its main components of PVC and stone powder. It resists mildew in wet conditions, making it a reliable choice for areas prone to moisture.



HIGH FIRE RESISTANCE

With a fire resistance rating of up to B1 level, second only to marble, the Artesian Woods Collection doesn't burn and helps prevent the spread of flames. It does not generate toxic gases in the case of a structure fire.



ANTI-SKID SURFACE

Designed for safety, this flooring features a super anti-skid surface. Compared to ordinary flooring materials, it offers stronger foot friction, reducing the risk of slipping even on wet floors.





BYRON LUXURY VINYL TILE

WILV0101 3.0 MM | 20 MIL





MELODY LUXURY VINYL TILE

WILV0102 3.0 MM | 20 MIL





LAYTON
LUXURY VINYL TILE

WILV0103
3.0 MM | 20 MIL





ASHWORTH LUXURY VINYL TILE

WILV0104 3.0 MM | 20 MIL





SOLSTICE LUXURY VINYL TILE

WILV0105 3.0 MM | 20 MIL





HOBART LUXURY VINYL TILE

WILV0106 3.0 MM | 20 MIL





TARA
LUXURY VINYL TILE

WILV0107
3.0 MM | 20 MIL

ARTESIAN WOODS



GLUE DOWN | 3.0 MM, 20 MIL

Construction	Luxury Vinyl Tile	
Classification	ASTMF 1700, Class III, Type B	
Dimensions	7" long x 60" wide, 177.8 mm x 1524 mm	
Overall Thickness	3.0 mm	
Wear Layer	20 mil	
Finish	Anti-Scratch & Anti-Microbial Coating	
Texture	Embossed	
Edge Profile	Micro Bevel	
Packaging	43.75 sf/ctn, 15 pcs/ctn, 55.3 lbs/ctn, 50 ctn/plt, 2187.5 sf/plt	


Installation & Maintenance

Glue Down

Ambient & Surface Temperature at Installation: 60 - 85 Degrees Fahrenheit

Maintenance: Neutral pH Cleaner

Test Method & Requirements			
Solid Vinyl Floor Tile	ASTM F1700	Pass	
Flexibility	ASTM F137	Pass	
Thickness	ASTM F386	Pass	
Wear Layer Thickness	ASTM F410	Pass	
Stain/Chemical Resistance	ASTM F925	Pass	
Resistance to Heat Color Change	ASTM F1514	Pass	
Resistance to Light Color Change	ASTM F1515	Pass	
Residual Indentation	ASTM F1914	Pass	
Size & Squareness	ASTM F2055	Pass	
Dimensional Stability w/Exposure to Heat	ASTM F2199	Pass	
Static Coefficient of Friction Polished Surface	ASTM D2047	Exceeds Standard	
Static Load Limit	ASTM F970	PASS >250 LBS	
Flammability/Radiant Flux	ASTM E648	Class I	
Smoke Density	ASTM E662	Pass	




Warranty

10 Year Commercial, 10 Year Multifamily Common Areas 30 Year Residential, 30 Year Multifamily Residence Areas

Layout Options:

ASHLAR



STAGGER

Health & Environment

FloorScore SCS Certified









