


Portland Collection

General Information

This product must be installed by professional installers that have sufficient professional liability insurance coverage (aka ‘Errors and Omissions’ insurance) for the project. Matter Surfaces recommends installing and maintaining entrance matting at all outdoor entrances and transitions from warehouse to office space; this will improve air quality and lengthen the life of floors.



Proper glides must be used on all furniture that may slide directly across the matting. Heavy objects must not be moved directly across the matting; use protective boards.

Direct sunlight can cause UV damage, such as fading, to most interior finishes. Low E glass should be selected to reduce the UV transmission to less than 1%. If Low E glass is not an option, applying 3M™ Sun Control Window Film, or similar, on the windows is recommended. Areas of the flooring subjected to direct sunlight must be shielded for two hours before, during and for a period of (72) hours after the installation.

Product	Entryway Matting
Construction	Tufted
Fiber	100% Econyl® Regenerated Polyamide 6 Nylon
Backing	Premium Vinyl
Use Class	Commercial 33
CleanZone™	Zone 3 Lobby
Recommended Adhesive	MI 3500
Roll Width	4’2” & 6’7”
Roll Length	82’
Pile Height	5.5 mm
Total Height	7.0 mm
Pile Weight	29.5 oz / ft²
Total Weight	99 oz / yd²

Performance		Result
Surface Flammability	Radiant Panel EN 13501-1	Class 1
Critical Radiant Flux	ASTM 648-1	Class 1

Sustainability information can be found at <https://products.ecomedes.com/products>

Warranty	Three Year Limited Warranty
----------	-----------------------------