



Topeka | SCLA0201



Augusta | SCLA0202




Lansing | SCLA0203




Lincoln | SCLA0204



Albany | SCLA0205



Harrisburg | SCLA0206



Richmond | SCLA0207



Jackson | SCLA0208

SPECIFICATIONS

Construction	Water Resistant Core Laminate
Classification	EN 13329
Dimensions	9.5" Wide x 60" Long
Overall Thickness	14 mm (includes 2.0 mm EVA Pad)
Wear Surface	AC4 Rated
Texture	Embossed
Edge Profile	4-Sided Painted Bevel
Packaging	23.29 sf/ctn, 44 ctn/plt. 1024.8 sf/plt
Installation	Angle/Angle
Warranty	15 Yr Light Commercial, 15 Yr Limited Multi-Family, Lifetime Residential, 80 hour Topical

INSTALLATION FAST FACTS

- Radiant Heat: Approved (Hydro Systems ONLY)
- Acclimation: 48 hrs unopened carton
- Moisture Content: Not to Exceed 2.5%
- Expansion Space: 3/8" gap
- Transitions not required in rooms up to 66' w or 66' long
- Inspect flooring prior to installation
- Use floor protection for furniture

Read Complete Instructions Before Installing



tasflooring.com

**SPEC SHEET
WARRANTY
INSTALLATION & MAINTENANCE
TRIMS, TRANSITIONS & QNOSE**

