TENACITY

TAS FLOORING

GLUE DOWN | 2.5 MM, 12 MIL



Compass | NOLV0601



Mimosa | NOLV0602



Primrose | NOLV0603



Gibraltar | NOLV0604



Sloop | NOLV0605



Gardenia | NOLV0606



Monitor | NOLV0607

SPECIFICATIONS

Construction	Luxury Vinyl Tile
Classification	ASTM F1700, Class III, Type B
Dimensions	7” Wide x 48” Long, 177.8 mm x 1219.2 mm
Overall Thickness	2.5 mm
Wear Layer	12 mil
Finish Coat	Polyurethane
Texture	Embossed
Edge Profile	Square Edge
Packaging	35 sf/ctn, 15 pcs/ctn, 30.5 lbs/ctn, 2100 sf/ctn, 60 ctn/plt
Installation	Glue Down - WF Taylor Pinnacle adhesive required
Warranty	5 Yr Light Commercial/Multifamily Common Areas, 25 Yr Residential/Multifamily Residence

INSTALLATION FAST FACTS

- Acclimate to Normal Room Conditions (NRC) 59°F - 95°F, RH Between 35% - 55%
- RH Between 35% - 55%
- Hydro Radiant Heat approved (≤ 85°F)
- Roll flooring immediately after installation in two directions, reroll 2 hours later
- Follow adhesive instructions for substrate moisture, coverage, PH, porosity, and open time
- Repair or replace worn trowel notches
- Insure floor flatness to within 1/8” in 6’

Read Complete Instructions Before Installing

SPEC SHEET
WARRANTY
INSTALLATION & MAINTENANCE

tasflooring.com

floor score
SCScertified

PHTHALATE FREE

Glue

Hydronic Heat

Additional specifications, full installation/maintenance and warranty information available online at **TASFLOORING.COM**.

A division of T&A supply company, Inc.