

RESONATE



SPC | 5.0 MM, 20 MIL



Ash | SCRC0201



Craft Oak | SCRC0202



Hickory | SCRC0203



Vernessa Oak | SCRC0204



Remmy Oak | SCRC0205



Walnut | SCRC0206



Acacia | SCRC0207



Warm Oak | SCRC0208

SPECIFICATIONS

Construction	SPC, Stone Polymer Composite, Rigid Core
Classification	ASTM F3261, Class I, Type B, Grade 1, Class B
Dimensions	7" Wide X 48" Long
Overall Thickness	5.0 mm (Includes 1 mm IXPE pad)
Wear Layer	20 MIL
Finish Coat	Low Gloss, Polyurethane
Texture	Smooth
Edge Profile	4-Sided Painted Bevel
Packaging	18.88 sf/ctn, 65 ctn/plt, 1227.2 sf/plt
Installation	Angle/Angle
Warranty	10 Yr Light Commercial, 10 Yr Multi-Family, 30 Yr Residential

INSTALLATION FAST FACTS

- Radiant Heat: Approved (Hydro Systems ONLY)
- Acclimate product to normal room conditions
- Recommended Room Temp: 60°F-85°F after install
- Expansion Space: 1/4" gap
- Transition required for rooms larger than 50'W x 50'L
- Subfloors dry and flat (3/16" in 10')

Read Complete Instructions Before Installing



tascontract.com

**SPEC SHEET
WARRANTY
INSTALLATION & MAINTENANCE
TRIMS, TRANSITIONS & QNOSE**



Additional Specifications, Full Installation Instructions & Warranty Information Available Online at TASCONTRACT.COM

A division of **TAS** supply company, Inc.

